KABLE LITE SURFACE TRANSFORMER-100W EL TECH LIGHTING

PRODUCT FEATURES



LAMPING

It can power lamps totaling up to 100 watts. The transformer is concealed inside a decorative housing with a fast acting secondary circuit breaker that will safely turn the system off should a short occur. Once the short has been removed the unit can be reset by simply flipping the wall switch off and back on.

Kable Lite Surface Transformer-100W EI LED



Kable Lite Surface Transformer-100W El LED

ORDERING INFORMATION

700SRT100E FINISH

S-LED SATIN NICKEL

As a general rule when using LED fixtures we do not recommend using greater than 70% of specified maximum wattage on the transformer due to inrush current. for assistance, please contact our technical support department.


| 700SRT100E | |
|------------|--|
| JOB NAME | |
| NOTES | |
| | |



KABLE LITE SURFACE TRANSFORMER-100W EL TECH LIGHTING LED

SPECIFICATIONS

| HARDWARE MATERIAL | | | | |
|-------------------|------------|--|--|--|
| SHADE MATERIAL | | | | |
| NET WEIGHT | | | | |
| HEIGHT | 2.2in | | | |
| WIDTH | 5.lin | | | |
| LENGTH | 5.lin | | | |
| WET LISTED | | | | |
| DAMP LISTED | | | | |
| DRY LISTED | | | | |
| GENERAL LISTING | ETL Listed | | | |
| INCLUDES | | | | |
| | · | | | |



LAMPING SPECIFICATIONS

| | LED LAMP | INTEGRATED LED | NON LED | NO LAMP |
|-----------------------|----------|----------------|---------|---------|
| DELIVERED LUMENS | | | | |
| WATTS | | | | |
| MAX WATTAGE PER BULB | | | 100W | |
| INPUT VOLTAGE | | | 120V | |
| DIMMING TYPE* | | | ELV | |
| ССТ | | | | |
| CRI | | | | |
| LED LIFETIME | | | | |
| L70 | | | | |
| AVERAGE BULB HOURS | | | | |
| FIELD SERVICEABLE LED | | | | |
| LAMP BASE | | | | |
| LAMP SHAPE | | | | |
| LAMP INCLUDED? | | | | |
| WARRANTY** | | | 5 Years | |

^{*} Dimming information available at www.techlighting.com/Downloads#dimming

T20/T24/JA8 INFORMATION

| | Integrated LED | Replacement LED Lamp | No Lamp * |
|---|-------------------|-------------------------|--------------|
| This product can be used to comply with | | | |
| California Building Energy Efficiency | | | N/A |
| Standards 2016 Title 24 Part 6 / JA8. | | | |
| This product can be used to comply with | | | |
| California Appliance Efficiency Standards | | | N1/A |
| 2016 Title 20 and may be shipped to and | H | | N/A |
| sold in California. | | | |

^{*}If a light fixture or component does not include a lamp or light source, it is the responsibility of the customer to select a lamp that meets the T24 and T20 requirements.



^{**} Visit techlighting.com for specific warranty limitations and details.