

WALL MONORAIL 4" ROUND POWER FEED CANOPY SINGLE-FEED

PRODUCT FEATURES



LAMPING

The low-voltage leads from the remote transformer connect to canopy leads inside the junction box.

Wall MonoRail 4" Round Power Feed Canopy Single-Feed



Wall MonoRail 4"
Round Power Feed
Canopy Single-
Feed

ORDERING INFORMATION

700WMOP4R SHAPE OR SIZE

4" ROUND

FINISH

Z ANTIQUE BRONZE

S SATIN NICKEL

W WHITE

700WMOP4R _____

JOB NAME _____


NOTES _____



WALL MONORAIL 4" ROUND POWER FEED CANOPY SINGLE-FEED

SPECIFICATIONS

| | |
|-------------------|------------|
| HARDWARE MATERIAL | |
| SHADE MATERIAL | |
| NET WEIGHT | 0.95 lbs |
| HEIGHT | 4in |
| WIDTH | 2in |
| LENGTH | 2in |
| WET LISTED | |
| DAMP LISTED | |
| DRY LISTED | |
| GENERAL LISTING | ETL Listed |
| INCLUDES | |



LAMPING SPECIFICATIONS

| | LED LAMP | INTEGRATED LED | NON LED | NO LAMP |
|-----------------------|----------|----------------|---------|---------|
| DELIVERED LUMENS | | | | |
| WATTS | | | | |
| MAX WATTAGE PER BULB | | | | |
| INPUT VOLTAGE | | | 0V | |
| DIMMING TYPE* | | | | |
| CCT | | | | |
| CRI | | | | |
| LED LIFETIME | | | | |
| L70 | | | | |
| AVERAGE BULB HOURS | | | | |
| FIELD SERVICEABLE LED | | | | |
| LAMP BASE | | | | |
| LAMP SHAPE | | | | |
| LAMP INCLUDED? | | | | |
| WARRANTY** | | | 1 Year | |

* Dimming information available at www.techlighting.com/Downloads#dimming

** Visit techlighting.com for specific warranty limitations and details.

T20 / T24 / JA8 INFORMATION

| | Integrated LED | Replacement LED Lamp | No Lamp * |
|--|----------------|----------------------|-----------|
| This product can be used to comply with California Building Energy Efficiency Standards 2016 Title 24 Part 6 / JA8 . | | | N/A |
| This product can be used to comply with California Appliance Efficiency Standards 2016 Title 20 and may be shipped to and sold in California. | | | Yes |

* If a light fixture or component does not include a lamp or light source, it is the responsibility of the customer to select a lamp that meets the T24 and T20 requirements.

