

## PRODUCT FEATURES

- High-tech display head that combines simplicity with practical technology
- Telephoto camera lens inspired design
- Highly customizable featuring a plethora of finishes, beam spreads, lamping and stem lengths
- Compatible with the free-jack or rail system also available by Tech Lighting
- Ideal for commercial and residential lighting applications
- Protected by a 5-year warranty



## LAMPING

Includes field replaceable 12 watt, 737.1 delivered lumen, 2700K, 3000K or 3500K field replaceable LED module. Dimmable with most LED compatible ELV or Triac dimmers. Choice of 18° or 40° field changeable optics. Integrated lens holder accommodates up to two MR16 sized lenses or louvers (sold separately). As a general rule when using the Burk head, we do not recommend using greater than 33% of the maximum wattage specified for the low voltage transformer due to inrush current requirements. For assistance in calculations, please contact Technical Support.

Aged Brass /  
Aged Brass



Antique Bronze /  
Antique Bronze

Black /  
Satin Nickel

Satin Nickel /  
Satin Nickel

White /  
Satin Nickel

To view all available finish options, please visit [techlighting.com](http://techlighting.com)

## ORDERING INFORMATION

700	SYSTEM	BRK	CRI	COLOR TEMP	BEAM SPREAD	LENGTH (A)	FINISH	LAMP
	FJ FREEJACK	8	80 CRI	27 2700K	20 18°	03 3"	R AGED BRASS	LED
	MP MONOPOINT	9	90 CRI	30 3000K	35 40°	06 6"	Z ANTIQUE BRONZE	
	MO MONORAIL			35 3500K			B BLACK	
							S SATIN NICKEL	
							W WHITE	

Note. MP includes 4 Round Flush Canopy. For custom stem lengths, please contact the Quotes Department.

700 \_\_\_\_\_ BRK \_\_\_\_\_

JOB NAME \_\_\_\_\_

NOTES \_\_\_\_\_


\_\_\_\_\_



# BURK HEAD

## SPECIFICATIONS

HARDWARE MATERIAL	Metal
SHADE MATERIAL	
NET WEIGHT	2 lbs
HEIGHT	3in
WIDTH	3.6in
LENGTH	3in
BEAM SPREAD	
UP LIGHT / DOWN LIGHT / BOTH?	
WET LISTED	
DAMP LISTED	
DRY LISTED	
MIN. HANGING HEIGHT	3in
MAX HANGING HEIGHT	3in
TOTAL CORD LENGTH	
SLOPED CEILING ADAPTABLE?	N/A
GENERAL LISTING	ETL Listed
INCLUDES	



## LAMPING SPECIFICATIONS

	LED LAMP	INTEGRATED LED	NON LED	NO LAMP
DELIVERED LUMENS	634.0			
WATTS	12			
MAX WATTAGE PER BULB	12W			
INPUT VOLTAGE	12V 120V			
DIMMING TYPE*	ELV, MLV			
CCT	2700K 3000K 3500K			
CRI	80 CRI 90 CRI			
LED LIFETIME				
L70	>50000			
AVERAGE BULB HOURS				
FIELD SERVICEABLE LED				
LAMP BASE	Integrated LED			
LAMP SHAPE	Integrated LED			
LAMP INCLUDED?	True			
WARRANTY**	5 Years			

\* Dimming information available at [www.techlighting.com/Downloads#dimming](http://www.techlighting.com/Downloads#dimming)

\*\* Visit [techlighting.com](http://techlighting.com) for specific warranty limitations and details.

## T20 / T24 / JA8 INFORMATION

	Integrated LED	Replacement LED Lamp	No Lamp *
This product can be used to comply with California Building Energy Efficiency Standards 2016 <b>Title 24</b> Part 6 / <b>JA8</b> .		No	
This product can be used to comply with California Appliance Efficiency Standards 2016 <b>Title 20</b> and may be shipped to and sold in California.		N/A	

\* If a light fixture or component does not include a lamp or light source, it is the responsibility of the customer to select a lamp that meets the T24 and T20 requirements.

