

MINI LAYLA 13 PENDANT

PRODUCT FEATURES


- A simple geometric ring and light module allows the LED source to illuminate up and down providing an unexpected twist to lighting up your space
- Available in three finishes, the Natural Brass that will patina over time, Satin Nickel, and a Nightshade Black
- Available in two sizes. 13" and 18" diameters
- Dimmable with most LED compatible ELV and TRIAC dimmers
- Includes 6 feet of field-cutttable cable to match finish selection
- Protected by a 5-year warranty, please visit the "About Us" Page on techlighting.com for more for warranty details



Nightshade Black

LAMPING

Includes 12 volt 6 watt 273 delivered lumen, 3000K, 90 CRI, LED module. Dimmable with low-voltage or magnetic dimmer (based on transformer). Includes 6 feet of field-cutttable cable. Nightshade black supplied with bronze cable. Brass and Satin nickel supplied with satin cable.



Natural Brass

Nightshade Black

Satin Nickel

ORDERING INFORMATION

| 700 | SYSTEM | LAY | SHAPE OR SIZE | FINISH | LAMP |
|-----|--------------|-----|---------------|--------------------|---|
| | FJ FREEJACK | | 13 13" SMALL | NB NATURAL BRASS | -LED930 INTEGRATED LED 90 CRI 3000K 12V |
| | MP MONOPOINT | | | B NIGHTSHADE BLACK | |
| | MO MONORAIL | | | S SATIN NICKEL | |

Note. Note. MP includes 4" Round Flush Canopy. Nightshade Black not available in MO.

700 _____ LAY _____

JOB NAME _____


NOTES _____



MINI LAYLA 13 PENDANT

SPECIFICATIONS

| | |
|-------------------------------|-------------|
| HARDWARE MATERIAL | Metal |
| SHADE MATERIAL | Aluminum |
| NET WEIGHT | 1.5 lbs |
| HEIGHT | 15.5in |
| WIDTH | 1.1in |
| LENGTH | 13.2in |
| UP LIGHT / DOWN LIGHT / BOTH? | |
| WET LISTED | |
| DAMP LISTED | |
| DRY LISTED | Yes |
| MIN. HANGING HEIGHT | 21.4in |
| MAX HANGING HEIGHT | 87.4in |
| SLOPED CEILING ADAPTABLE? | Yes 45° Max |
| GENERAL LISTING | ETL Listed |
| INCLUDES | |



LAMPING SPECIFICATIONS

| | LED LAMP | INTEGRATED LED | NON LED | NO LAMP |
|-----------------------|----------|----------------|---------|---------|
| DELIVERED LUMENS | | 219.0 | | |
| WATTS | | 6.6 | | |
| MAX WATTAGE PER BULB | | 6.6W | | |
| INPUT VOLTAGE | | 12V 120V | | |
| DIMMING TYPE* | | ELV, MLV | | |
| CCT | | 3000K | | |
| CRI | | 90 CRI | | |
| LED LIFETIME | | >50000 | | |
| L70 | | | | |
| AVERAGE BULB HOURS | | | | |
| FIELD SERVICEABLE LED | | | | |
| LAMP BASE | | Integrated LED | | |
| LAMP SHAPE | | Integrated LED | | |
| LAMP INCLUDED? | | True | | |
| WARRANTY** | | 5 Years | | |

* Dimming information available at www.techlighting.com/Downloads#dimming

** Visit techlighting.com for specific warranty limitations and details.

T20 / T24 / JA8 INFORMATION

| | Integrated LED | Replacement LED Lamp | No Lamp * |
|--|----------------|----------------------|-----------|
| This product can be used to comply with California Building Energy Efficiency Standards 2016 Title 24 Part 6 / JA8 . | Yes | | |
| This product can be used to comply with California Appliance Efficiency Standards 2016 Title 20 and may be shipped to and sold in California. | N/A | | |

* If a light fixture or component does not include a lamp or light source, it is the responsibility of the customer to select a lamp that meets the T24 and T20 requirements.

