



Catalog Number	
Project	Type

FEATURES & SPECIFICATIONS

APPLICATION — The CEL Canopy light was designed for mid to high level lighting under storefront awnings, or any surface mount general lighting application. The welded seams provide a smooth constructed look that can be integrated into any design concept. This fixture is perfect when a finished, rather than industrial appearance is needed.

CONSTRUCTION — The fixture is constructed of .12" thick extruded aluminum with a welded seam. The hinged door frame is constructed of extruded aluminum with mitered corners to fit the glass lens. A Polyethylene Foam gasket is used for a watertight seal.

FINISH — A Super Durable Polyester powder coat finish is electrostatically applied in our state of the art paint facility. Standard colors available: Black, Bronze, US Green, White. Custom colors available upon request.


OPTICAL SYSTEM — High quality faceted aluminum reflector. Flat glass, flat prismatic, and drop lenses available. Lamps burn in horizontal position.

ELECTRICAL SYSTEM — Provided with a 4KV pulse rated socket assembly. Fixtures are available with a 250W-400W Metal Halide, and 250W-400W HPS lamp and ballast system. Each 60HZ CWA multi-tap, 480V, or Fluorescent ballast is pre-wired and installed for convenience.

MOUNTING — Permanently mounted via four .25" mounting holes and hardware pack provided by Techlight. Two (2) .88" conduit entries are provided



Large Extruded Canopy CEL SERIES



Series	Housing Height	Length & Width
CEL	7.01"	21.63" x 21.63"

ORDERING INFORMATION

Choose the bold face options for the appropriate luminaire configuration for your application and enter on the line above each fixture attribute. Accessories may be factory installed, depending on the particular accessory chosen, but still be ordered as a separate line item.

Example: **CEM400M-MT-F-WH**

CEL		-		-		-		-	
Series	Wattage/Source	Voltage	Lens	Pulse-Start	Finish				
CEL	250M 250W Metal Halide 250H 250W High Pressure Sodium 400M 400W Metal Halide 400H 400W High Pressure Sodium	MT Multi-Tap ¹ 480 480V	F Flat Glass FP Flat Prismatic D Drop Lens	PS Pulse-Start	BK Black BZ Bronze GR OD Green USG US Green WH White SP Special ²				

NOTES

- Multi-Tap is 120/208/240/277V wired 277V.
- Custom RAL color matching is available. Contact your Techlight sale representative for additional information.