



Catalog Number	
Project	Type

## FEATURES & SPECIFICATIONS

**APPLICATION** — The CVM Canopy light was designed for mid-level lighting under storefront awnings, I-Beam mounting, or any surface mount general lighting application. The welded seams provide a smooth constructed look that can be integrated into any design concept. Quick release hinges make access for maintenance easy.

**CONSTRUCTION** — The fixture is constructed of .12" thick extruded aluminum with a welded seam. The hinged door frame is constructed of extruded aluminum with mitered corners to fit the lens. A Polyethylene Foam gasket is used for a watertight seal.

**FINISH** — A Super Durable Polyester powder coat finish is electrostatically applied in our state of the art paint facility. Standard colors available: Black, Bronze, US Green, White. Custom colors available upon request.


**OPTICAL SYSTEM** — High quality faceted aluminum reflector designed around a vertical lamp orientation. Flat prismatic lens standard.

**ELECTRICAL SYSTEM** — Provided with a 4KV pulse rated socket assembly. Fixtures are available with a 150W-400W Metal Halide lamp and ballast system. Each 60HZ CWA multi-tap, 480V, or Fluorescent ballast is pre-wired and installed for convenience.

**MOUNTING** — Permanently mounted via four .25" mounting holes and hardware pack provided by Techlight. Two (2) .88" conduit entries are provided



## Medium Vertical Burn Extruded Canopy CVM SERIES



Series	Housing Height	Length & Width
<b>CVM</b>	10.10"	16.20" x 16.20"

## ORDERING INFORMATION

Choose the bold face options for the appropriate luminaire configuration for your application and enter on the line above each fixture attribute. Accessories may be factory installed, depending on the particular accessory chosen, but still be ordered as a separate line item.

Example: **CVM250M-MT-FP-WH**

CVM		-		-		-		-	
Series	Wattage/Source	Voltage	Lens	Pulse-Start	Finish				
<b>CVM</b>	<b>150M</b> 150W Metal Halide <b>200M</b> 200W PS Metal Halide <b>250M</b> 250W Metal Halide <b>320M</b> 320W PS Metal Halide <b>400M</b> 400W Metal Halide	<b>MT</b> Multi-Tap <sup>1</sup> <b>480</b> 480V	<b>FP</b> Flat Prismatic	<b>PS</b> Pulse-Start	<b>BK</b> Black <b>BZ</b> Bronze <b>GR</b> US Green <b>WH</b> White <b>SP</b> Special <sup>2</sup>				

### NOTES

- Multi-Tap is 120/208/240/277V wired 277V.
- Custom RAL color matching is available. Contact your Techlight sale representative for additional information.