



# LVSS1200 SERIES

## 1200Watt Stainless Steel Enclosure

Catalog Number	
Project	Type

### FEATURES & SPECIFICATIONS

**APPLICATION** — The LVSS1200 was designed to be the toughest and most durable transformer enclosure possible. The stainless steel exterior and gasketed captive door makes it ideal for the harshest of environments. It features a fully encapsulated 1200W low voltage transformer.

**CONSTRUCTION** — Constructed heavy duty stainless steel with captive hinged door.

**MOUNTING** — Keyhole mounts are provided on the backside of the enclosure for quick and secure mounting. Custom finishes available upon request.

**ELECTRICAL SYSTEM** — A 6-ft 16/3 SJ TW cord with a grounded straight blade plug comes standard. Field installable timer and photocells are available. Each unit is provided with four ¾" and one ½" knockouts on the underside for low voltage exit, and two ½" knockouts on each side for accessory mounting. Two terminal blocks with color coded secondaries include 12V, 12V, 13V, 14V, 15V, 24V, and 2 COM output taps on each block.

**LISTINGS** — ETL listed for wet locations.

**WARRANTY** — The complete luminaire is covered by a 3-year limited warranty.



SERIES	LENGTH, WIDTH & HEIGHT
<b>LVSS1200</b>	12.75" x 6.5" x 6.5"

### ORDERING INFORMATION


Choose the bold face options for the appropriate luminaire configuration for your application and enter on the line above each fixture attribute. Accessories may be factory installed, depending on the particular accessory chosen, but still be ordered as a separate line item.

**EXAMPLE:**

**LVSS1200M**

PART NUMBER	DESCRIPTIONS
<b>LVSS1200M</b>	1200W 120V INPUT XFMR

### DIMENSIONS



### ACCESSORIES

**TLHB800RCH**  
Digital Timer



**TLTN111**  
Mechanical Timer



**PSJ163**  
16 Gauge 3 Strand Lead Wire



**PCCORD-6** 6' Photocell Extension Cord  
**PCCORD-8** 8' Photocell Extension Cord



**P20000PC-LVENC**  
Photocell (DC Transformer Operation Only)

