



Catalog Number	
Project	Type

## FEATURES & SPECIFICATIONS

**APPLICATION** — Techlight's line of low bays was designed for light manufacturing, warehouse, retail, assembly lines, or production environments. The acrylic drop reduces shadows and provides a wide uniform distribution.

**CONSTRUCTION** — Heavy duty die cast aluminum housing with a white polyester powdercoat finish. Spun aluminum reflector and collar assembly. ETL and CETL Listed.

**FINISH** — A Super Durable Polyester powder coat finish is electrostatically applied in our state of the art paint facility. Standard colors available: White. Custom colors<sup>1</sup> available upon request.


**OPTICAL SYSTEM** — The aluminum reflector focuses light downward on working surfaces. The drop lens spreads the downward light evenly in a wide symmetric pattern. Designed for mid to low range mounting heights.

**ELECTRICAL SYSTEM** — Available in 150W thru 400W standard metal halide, pulse-start metal halide, and high pressure sodium. Comes standard with a 4KV pulse rated mogul base socket. Each 60HZ CWA multi-tap<sup>2</sup> or 480V ballast is pre-wired and installed for convenience.

**MOUNTING** — Splice box for direct hard wire, hook, cord, and plug assembly, or pendant mount.



## 16" Low Bay TL16M SERIES



Series	Housing Height	Length & Width
<b>TL16M</b>	23.00"	16.00" x 16.00"

## ORDERING INFORMATION

Choose the bold face options for the appropriate luminaire configuration for your application and enter on the line above each fixture attribute. Accessories may be factory installed, depending on the particular accessory chosen, but still be ordered as a separate line item.

Example: **TL16M-5-3-0**

Series	Wattage/Source		Lamp		Options
<b>TL16M</b>	<b>1</b> 175W Metal Halide MT	<b>14</b> 400W Metal Halide 480V	<b>1</b> MH175U	<b>12</b> MPR400/VBU/HO/O	<b>0</b> None
	<b>2</b> 175W Metal Halide 480V	<b>15</b> 400W PS Metal Halide MT	<b>2</b> MH175UPS	<b>13</b> CMH250/C/N/PA/O	<b>1</b> Mounting Hook
	<b>3</b> 175W PS Metal Halide MT	<b>16</b> 400W PS Metal Halide 480V	<b>3</b> MH250U	<b>14</b> CMH150/U/MED-O	<b>2</b> Hook and 6' Cord
	<b>4</b> 175W PS Metal Halide 480V	<b>17</b> 150W High Pressure Sodium MT	<b>4</b> MH250UPS	<b>15</b> CMH150CU942MEDO	<b>3</b> 120V Hook, Cord and Plug
	<b>5</b> 250W Metal Halide MT	<b>18</b> 150W High Pressure Sodium 480V	<b>5</b> MH320UPS	<b>16</b> MP320MHBUE37PS	<b>4</b> 208V/240V Hook, Cord and Plug
	<b>6</b> 250W Metal Halide 480V	<b>19</b> 250W High Pressure Sodium MT	<b>6</b> MH350UPS	<b>17</b> MCP250/C/PS/BU	<b>5</b> 277V Hook, Cord and Plug
	<b>7</b> 250W PS Metal Halide MT	<b>20</b> 250W High Pressure Sodium 480V	<b>7</b> MH400UED28		<b>6</b> 480V Hook, Cord and Plug
	<b>8</b> 250W PS Metal Halide 480V	<b>21</b> 400W High Pressure Sodium MT	<b>8</b> MH400UPS		
	<b>9</b> 320W PS Metal Halide MT	<b>22</b> 400W High Pressure Sodium 480V	<b>9</b> HPS150		
	<b>10</b> 320W PS Metal Halide 480V	<b>23</b> 150W PS Metal Halide MT	<b>10</b> HPS250		
	<b>11</b> 350W PS Metal Halide MT	<b>24</b> 150W PS Metal Halide 480V	<b>11</b> HPS400		
	<b>12</b> 350W PS Metal Halide 480V				
	<b>13</b> 400W Metal Halide MT				

### Accessories (Order as separate line items)

<b>THBH</b>	Mounting Hook	<b>THBSC1</b>	12" Reflector Safety Chain
<b>THBHC6</b>	6' PJ16/3 Cord	<b>THBSC6</b>	6' Ballast Pod Safety Chain
<b>THBSPM</b>	Swivel Pendant Mount	<b>THB16WG</b>	16" Wire Guard
<b>THBSTEM18</b>	18" Rigid Pendant		

### NOTES

- 1 Custom RAL color matching is available. Contact your Techlight sale representative for additional information.
- 2 Multi-Volt is 120/208/240/277V wired 277V unless specified otherwise.

# TL16M 16" Low Bay

---

## MOUNTING ACCESSORIES

---

**THBH**  
Mounting Hook



**THBSTEM18**  
18" Rigid Pendant



**THBHC6**  
6' PJ16/3 Cord



**THBSC1**  
12" Reflector Safety Chain



**THBSPM**  
Swivel Pendant Mount



**THBSC6**  
6' Ballast Pod Safety Chain




---

## ADDITIONAL FIXTURE ACCESSORIES

---

**THB16WG**  
16" Wire Guard



Techlight, Inc.  
2707 Satsuma Drive  
Dallas, TX, 75229  
Phone: 214-350-0591, 800-225-0727, Fax: 214-350-9137  
[www.techlight.com](http://www.techlight.com)