

Catalog Number	
Project	Туре

FEATURES & SPECIFICATIONS

APPLICATION —The lanscape burial light are the most versatile fixtures on the market. Various beam spreads and wattages allow for a customized finish to any property. The high end residential grade system was designed for 120V operation residential applications.

CONSTRUCTION — The die cast aluminum, brass, or zinc housings suspend from the covering grill by two steel spring clips. The grill is secured to the well sleeve with two self-tapping screws.

OPTICAL SYSTEM — A high-impact tempered glass lens is sealed to the housing using silicone for a watertight seal. The aluminum or brass safety grill rotates 360° for glare control.

ELECTRICAL SYSTEM — Each fixture is pre-wired with either 15' or 30' of 16/3 cable and is internally grounded. 70W thru 175W mercury vapor or metal halide light sources are available. Fixtures can be ordered less a ballast and lamp for incandescent operation.

MOUNTING — Fixtures are designed to be in-ground well lights and should be installed according to the installation instructions made available by Techlight. Proper drainage and substrate must be provided for water to flow freely through the well sleeve.

VL SERIES

Large HID/Incandescent Burial Light



 $\textbf{LISTINGS} - \mathsf{ETL} \ \mathsf{listed} \ \mathsf{for} \ \mathsf{wet} \ \mathsf{locations}. \ \mathsf{Meets} \ \mathsf{US} \ \mathsf{and} \ \mathsf{Canadian} \ \mathsf{safety} \ \mathsf{standards}.$

ORDERING INFORMATION

Choose the bold face options for the appropriate luminaire configuration for your application and enter on the line above each fixture attribute. Accessories may be factory installed, depending on the particular accessory chosen, but still be ordered as a separate line item.

EXAMPLE:

WLAR4 15-1 1 1 5 5

SERIES	CORD	SLEEVE	GRILL	1 2227	BALLAS ^{1, 2}
SERIES	CORD	SLEEVE	GRILL	LAMP ¹	BALLAS ", -
WLAR4 = Aluminum body WLBR4 = Brass body WLZR4 = Zinc body	15-1 = 15' Cord 30-1 = 30' Cord	1 = Burial Light Sleeve	1 = Aluminum Grill 2 = Brass Grill	BLANK = INCANDESCENT 1 = 100W R40 MV 4 = 175W R40 MV	2 = 100W MV QUAD 4 = 175W MV QUAD

NOTES

- 1 100W Max Wattage Allowed in Brass WLBR4 and Zinc
- 2 All ballasts listed here come in a medium steel enclosure.


ACCESSORIES (Order as separate line items) TLHB800RCH

Digital Timer



AVAILABLE FIXTURE DIMENSIONS

Dimensions shown are for fixture bodies only. Mounting ptions must be ordered separately.







www.techlight.com