


NON-CORROSIVE



206VC-WH



EXTENDS: 5 3/4"
H/CTR: 2 3/8"
BACKPLATE: 4 7/8" RD.

GUIDE: 206VC-WH-PC


ITEM #	LENS	LIGHT SOURCE	COLOR	OPTION
206VC	ACRYLIC Clear Glacier	INCANDESCENT (1) 60W MAX Medium Base	BK-Black WH-White	PC-Photocell (GU24 & LED only)
		LED LIGHT SOURCE		
		120V LIGHTWAVE LED LR12-13W 1000lm	CCT C-4K	
		E26 MEDIUM BASE LED LE26-A19 800lm	W-3K	

**Title 24
& GU24
Available**
(call for details)



208SL-BK

(Opal Beveled Shown)



EXTENDS:
8 1/2"
H/CTR:
10 5/8"
BACKPLATE:
4 5/8" x 4 5/8"

GUIDE: 208SC-LR12W-BK-PC


ITEM #	LENS	LIGHT SOURCE	COLOR	OPTION
208S	ACRYLIC C-Clear Glacier B-Clear Beveled L-Opal Beveled	INCANDESCENT (1) 60W MAX Medium Base	BK-Black WH-White	PC-Photocell
		LED LIGHT SOURCE		
		120V LIGHTWAVE LED LR12-13W 1000lm	CCT C-4K	
		E26 MEDIUM BASE LED LE26-A19 800lm	W-3K	

Title 24 & GU24 Available
(call for details)



208TC-WH

(Clear Glacier Shown)



I.D. = 3"



GUIDE: 208TC-WH

ITEM #	LENS	LIGHT SOURCE	COLOR
208T	ACRYLIC C-Clear Glacier B-Clear Beveled L-Opal Beveled	INCANDESCENT (1) 60W MAX Medium Base	BK-Black WH-White
		LED LIGHT SOURCE	
		120V LIGHTWAVE LED LR12-13W 1000lm	CCT C-4K
		E26 MEDIUM BASE LED LE26-A19 800lm	W-3K

Title 24 & GU24 Available
(call for details)



Posts accommodate Photo Control 320 or 688. See page 69 Posts sold separately.

SPEC SHEETS AND IES FILES AVAILABLE ONLINE. Specifications subject to change without notice. LED option information on page 6.