


OUTDOOR WALL FIXTURE 216/217



EXTENDS:
5 3/4"
H/CTR:
2 3/8"
BACKPLATE:
4 3/4" x 4 1/2"



Wave Lighting's 216/217 adds a contemporary look to any outdoor space. This fixture can be used to comply with 2016 Title 24 Part 6 High Efficacy LED Light Source Requirements. Wave Lighting's 216/217 is designed for wall applications and mounting hardware is included. Options include photocell.

LED SOURCE OPTIONS

LIGHTWAVE LED - LR/LT

- 120V, 50/60 Hz
- AC Driver-On-Board Array
- Estimated 50,000 Hrs L₇₀
- Low Flicker (LT models)
- Surge Supression
- Dimmable (see compatible dimmer list)
- High Efficacy LED Light Source
- 3000K or 4000K CCT; 80 or 90CRI
- 5 Year Warranty
- Energy Star

LED MULTI-VOLT SYSTEM - L11

- 120-277V, 50/60Hz
- Estimated 50,000 Hrs L₇₀
- 4000K CCT 80CRI
- 3 Year Warranty
- Energy Star

E26 REPLACEABLE LED - LE26

- 120V, 50/60Hz
- "Screw-In" Medium Base A19/E26 LED Lamp
- Estimated 15,000 Hrs L₇₀
- Low Flicker (3K models)
- Dimmable (see compatible dimmer list)
- 3000K CCT 90CRI or 4000K CCT 80CRI
- 3 Year Warranty
- Energy Star







SPECIFICATIONS

- Black or White
- Mounting Hardware Included
- Opal Acrylic Diffuser
- Wall Mount Only
- Minimum Starting Temp -20°F
- UL Listed for Wet Locations

GUIDE: 217-BK-LR12W-PC

CALL FOR PHOTOMETRIC INFORMATION

ITEM #	LENS	COLOR	LIGHT SOURCE	OPTION
216	ACRYLIC Clear Prism	BK-Black WH-White	INCANDESCENT (1) 60W MAX Medium Base	PC-Photocell (NOT AVAILABLE W/ L11)
			LED LIGHT SOURCE	
217	Opal		LIGHTWAVE LED LR12-13W 1000lm 80CRI  LT12-12W 1040lm 90CRI 	CCT C-4K W-3K
			LED MULTI-VOLT SYSTEM L11-11W 912lm 	4K
			E26 REPLACEABLE LED LE26-10W 800lm 	C-4K W-3K

★ Lamp Included  Energy Star Qualified Product

REFER TO CATALOG FOR OPTION SPECIFICATIONS - Specifications subject to change without notice - FIXTURE SPEC 1/19