




PROJECT \_\_\_\_\_

TYPE \_\_\_\_\_

VOLTAGE \_\_\_\_\_

# OUTDOOR SECURITY FIXTURE 263FMF

Wave Lighting's 263FMF adds a welcoming look to any outdoor space. This fixture can be used to comply with 2016 Title 24 Part 6 High Efficacy LED Light Source Requirements. Wave Lighting's 263FMF is designed for wall or ceiling applications and mounting hardware is included.



## LED SOURCE OPTIONS

### LIGHTWAVE LED - LR/LT

- 120V, 50/60 Hz
- AC Driver-On-Board Array
- Estimated 50,000 Hrs L<sub>70</sub>
- Low Flicker (LT models)
- Surge Supression
- Dimmable (see compatible dimmer list)
- High Efficacy LED Light Source
- 3000K or 4000K CCT; 80 or 90CRI
- 5 Year Warranty
- Energy Star

### E26 REPLACEABLE LED - LE26

- 120V, 50/60Hz
- "Screw-In" Medium Base A19/E26 LED Lamp
- Estimated 15,000 Hrs L<sub>70</sub>
- Low Flicker (3K models)
- Dimmable (see compatible dimmer list)
- 3000K CCT 90CRI or 4000K CCT 80CRI
- 3 Year Warranty
- Energy Star







## SPECIFICATIONS

- White Powdercoated Aluminum
- Mounting Hardware Included
- Frosted Prismatic Diffuser
- Wall or Ceiling Mount
- Minimum Starting Temp -20°F
- UL Listed for Wet Locations

GUIDE: 263FMF-LR12W-WH

CALL FOR PHOTOMETRIC INFORMATION

ITEM #	LENS	LIGHT SOURCE	COLOR	
263FM	ACRYLIC F-Frosted Prismatic	INCANDESCENT (1) 40W MAX Medium Base	WH-White	
		LED LIGHT SOURCE		
		LIGHTWAVE LED LR12-13W 1000lm 80CRI  LT12-12W 1040lm 90CRI 		CCT C-4K W-3K
		E26 REPLACEABLE LED LE26-10W 800lm  		C-4K W-3K

 Lamp Included  Energy Star Qualified Product

REFER TO CATALOG FOR OPTION SPECIFICATIONS - Specifications subject to change without notice - FIXTURE SPEC 1/19