



C2014TP-



STYLE A FITTER

C2014T Polycarbonate Globe
C8014T Acrylic Globe



STYLE B FITTER

C2024T Polycarbonate Globe
C8024T Acrylic Globe

C8024TC-

(shown with R3)



Globes have 8" Neck. See Page 81 for Replacements



GUIDE: C2014TL-L40C-BK-T3



ITEM #	ACORN	LIGHT SOURCE	COLOR	OPTIONS
C2014T-Style A C2024T-Style B	POLYCARBONATE C-Clear L-Opal S-Smoke P-Clear Prism	LED LIGHT SOURCE 120-277v DEDICATED LED L40-40W 4000lm L60-60W 6000lm E39 CORN COB LED 100-277v LC5-54W 7290lm, Type 5 ☆ LC3-40W 5600lm, Type 3 ☆ LCD-54W 5900lm, Dark Sky ☆	BK-Black BZ-Bronze WH-White CCT C-4K(standard) W-3K(special order) B-5K(special order)	D- 0-10V Dimming (Dedicated LED Only) T3-Type III Distribution (Dedicated LED Only, T3 is Special Order, Type V Standard)
C8014T-Style A C8024T-Style B	ACRYLIC C-Clear L-Opal S-Smoke P-Clear Prism		CCT C-4K(standard)	

Commercial LED standard in 4000K, Type V, other options available upon request. Integral surge suppression. 5 year warranty on LED components.

Posts sold separately.



4Kv medium base socket standard in HID, Mogul Upon Request.

120V HPF integral ballast standard in HID models, specify voltage for multi-tap.

☆ Lamp Included

GUIDE: C2014TL-150MH-BK-HS



ITEM #	ACORN	LIGHT SOURCE	COLOR	OPTIONS
C2014T-Style A C2024T-Style B	POLYCARBONATE C-Clear L-Opal S-Smoke P-Clear Prism	INCANDESCENT (1) 200W MAX Medium Base HPF MAGNETIC BALLAST 100MH-(1) 100W Metal Halide ☆ 150MH*-(1) 150W Metal Halide ☆	BK-Black BZ-Bronze WH-White	DSR-Dark Sky Reflector HS-House Shield MG-E39 Mogul Socket MT208-208v Multi-Tap MT240-240v Multi-Tap MT277-277v Multi-Tap R3-Type III Refractor R5-Type V Refractor (See Page 70 for Light Distribution)
C8014T-Style A C8024T-Style B	ACRYLIC C-Clear L-Opal S-Smoke P-Clear Prism	100H-(1) 100W HPS ☆ 150H*-(1) 150W HPS ☆		

*Not available with C8014T or C8024T

SPEC SHEETS AND IES FILES AVAILABLE ONLINE. Specifications subject to change without notice. LED option information on page 6.