


- LED & HID Models
- 0-10V Dimming LED Options
- LED Models Are DLC Listed


C2015TL-



I.D. = 3"

STYLE A FITTER

C2015T C8015T
Polycarbonate Globe Acrylic Globe



I.D. = 3"

STYLE B FITTER

C2025T C8025T
Polycarbonate Globe Acrylic Globe

Globes have 8" Neck, See Page 81 for Replacements



Commercial LED standard in 4000K, Type V, other options available upon request. Integral surge suppression. 5 year warranty on LED components.

24", 27", 30" & 36" Globes Available
Contact Sales for Details

GUIDE: C2015TC-L40C-BK



ITEM #	ACORN	LIGHT SOURCE	COLOR	OPTIONS	
C2015T -Style A C2025T -Style B	POLYCARBONATE C-Clear L-Opal S-Smoke P-Clear Prism	LED LIGHT SOURCE		BK -Black BZ -Bronze WH -White	D 0-10V Dimming (Dedicated LED Only) T3 -Type III Distribution (Dedicated LED Only, T3 is Special Order, Type V Standard)
		120-277v DEDICATED LED L40 -40W 4000lm L60 -60W 6000lm	CCT C -4K(standard) W -3K(special order) B -5K(special order)		
C8015T -Style A C8025T -Style B	ACRYLIC C-Clear L-Opal S-Smoke P-Clear Prism	E39 CORN COB LED 100-277v		CCT C -4K(standard)	
		LC5 -54W 7290lm, Type 5 ☆ LC3 -40W 5600lm, Type 3 ☆ LCD -54W 5900lm, Dark Sky ☆			



GUIDE: C2015TC-150MH-BK-HS



ITEM #	ACORN	LIGHT SOURCE	COLOR	OPTIONS
C2015T -Style A C2025T -Style B	POLYCARBONATE C-Clear L-Opal S-Smoke P-Clear Prism	INCANDESCENT (1) 200W MAX Medium Base	BK -Black BZ -Bronze WH -White	DSR -Dark Sky Reflector HS -House Shield MG -E39 Mogul Socket MT208 -208v Multi-Tap MT240 -240v Multi-Tap MT277 -277v Multi-Tap R3 -Type III Refractor R5 -Type V Refractor (See Page 70 for Light Distribution)
		HPF MAGNETIC BALLAST 100MH -(1) 100W Metal Halide ☆ 150MH -(1) 150W Metal Halide ☆		
C8015T -Style A C8025T -Style B	ACRYLIC C-Clear L-Opal S-Smoke P-Clear Prism	100H -(1) 100W HPS ☆ 150H -(1) 150W HPS ☆		

4Kv medium base socket standard in HID, Mogul Upon Request.

120V HPF integral ballast standard in HID models, specify voltage for multi-tap.

☆ Lamp Included

SPEC SHEETS AND IES FILES AVAILABLE ONLINE. Specifications subject to change without notice. LED option information on page 6.

FAX 330.630.1994 • WWW.WAVELIGHTING.COM