


OUTDOOR POST FIXTURE S75TC/L-2



Wave Lighting's S75TC/L-2 adds a welcoming look to any outdoor space. This fixture can be used to comply with 2016 Title 24 Part 6 High Efficacy LED Light Source Requirements. Wave Lighting's S75TC/L-2 fits on a 3" diameter pole (sold separately) only mounting hardware is included. Options include photocell.

LED SOURCE OPTIONS

LIGHTWAVE LED - LR/LT

- 120V, 50/60 Hz
- AC Driver-On-Board Array
- Estimated 50,000 Hrs L₇₀
- Low Flicker (LT models)
- Surge Suppression
- Dimmable (see compatible dimmer list)
- High Efficacy LED Light Source
- 3000K or 4000K CCT; 80 or 90CRI
- 5 Year Warranty

LED MULTI-VOLT SYSTEM - L22

- 120-277V, 50/60Hz
- Estimated 50,000 Hrs L₇₀
- 4000K CCT 80CRI
- 3 Year Warranty

E26 REPLACEABLE LED - LE26

- 120V, 50/60Hz
- "Screw-In" Medium Base A19/E26 LED Lamp
- Estimated 15,000 Hrs L₇₀
- Low Flicker (3K models)
- Dimmable (see compatible dimmer list)
- 3000K CCT 90CRI or 4000K CCT 80CRI
- 3 Year Warranty



SPECIFICATIONS

- Black or White
- Mounting Hardware Included
- Clear Prismatic or Opal Acrylic Diffuser
- Post Mount Only
- Minimum Starting Temp -20°F
- UL Listed for Wet Locations

CALL FOR PHOTOMETRIC INFORMATION

GUIDE: S75TC-2-BK-PC

ITEM #	DIFFUSER	LIGHT SOURCE	COLOR	OPTION	
S75T	ACRYLIC C-2-Clear Prismatic L-2-Opal	INCANDESCENT (2) 60W MAX Medium Base	BK-Black WH-White	PC-Photocell (NOT AVAILABLE W/ L22)	
		LED LIGHT SOURCE			
		LIGHTWAVE LED LR12-(2)13W 1000lm 80CRI LT12-(2)12W 1040lm 90CRI			CCT C-4K W-3K
		LED MULTI-VOLT SYSTEM L22-22W 1824lm			4K
E26 REPLACEABLE LED LE26-(2)10W 800lm ☆	C-4K W-3K				

☆ Lamp Included

REFER TO CATALOG FOR OPTION SPECIFICATIONS - Specifications subject to change without notice - FIXTURE SPEC 1/19