

FLUTE

870mm x 100mm 36mm thickness


10 tiles / Lm


Finish: Silk

Suitability: Wall Indoor & Covered outdoor use



FLUTE TILE TECHNICAL DATA SHEET







Saint ,Silk Finish

Limesite is subject to variation in hue shade & texture. Refer to this image as an indication of the appearance & colour tone only

TECHNICAL DATA

DIMENSIONS	870mm x 100mm		THICKNESS	36mm						
LENGTH	10 tiles/Lm	0.1m/tile	WEIGHT	±55 kg/Lm ±5.5 kg/tile						
COLOURS	Origins Meraki Seasonal range (see website for full colour range)*									
FINISH	Silk									
MATERIAL	Limesite™ (high performance, integrally coloured concrete)									
SUITABILITY	Indoor Covered outd	oor use	USE	Wall						

PACKAGING

BOX DIMENSIONS		вох			CRATE			CRATE			
L	W	Н	tiles	area	weight	L	W	Н	boxes	area	weight
N/A	N/A	N/A	N/A	N/A	N/A	*	*	*	*	*	*

- *Packaging data is dependant on the order quantity. Flute tiles are securely packed in packed in custom crates to gurantee safe handling during transit.
- $\bullet \ \text{The Flute Tile features a 5 degree taper on both sides Facilitating smoother tilling around a curve.}\\$
- The weight of the tile may necessistate support during installation to prevent any issue, especially if it's installed in a floating manner without direct floor support


 $Limesite^{\texttt{M}} \ tiles \ are \ suitable \ for \ outdoor \ use \ provided \ they \ are \ installed \ in \ a \ covered \ setting \ that \ offers \ protection \ from \ direct \ sunlight.$

- •*Colour variance is an inherent property of our products as they are handmade and colour may vary from tile to tile. The onus is on the client to confirm colours by looking at physical samples and completed projects.
- $\bullet \ \text{Custom colour development is available on request. Please refer to the website for more information}.$
- "Wolkberg recommends applying a protective nano coat layer of Wolkseal Diamond over tiles and grouting post installation. Please refer to the website for Care & Maintenance details.

Disclaimer: All data is based on averages as our products are handmade and can vary from tile to tile.

For more information email: design@wolkberg.com

FLUTE TILE TILING LAYOUT POSSIBILITIES



- 1.
- $\bullet \ \text{The Flute Tile features a 5 degree taper on both sides Facilitating smoother tilling around a curve.}\\$
- The weight of the tile may necessistate support during installation to prevent any issue, especially if it's installed installed in a floating manner without direct floor support.

TILE DISCLAIMER

DISCLAIMER

- These have been tried and tested for use in all indoor environments ,covered outdoor environments, fireplaces, and wet areas. There are some limitations and must be considered in specification stage:
- •We do not recommend the product for full outdoor use as the suns UV rays will definitely deteriorate the sealer resulting in either discoloration or pealing off.
- •While the tiles are integrally coloured the full sun rays can lighten the pigment over time.
- •The above is true for almost all surfaces where manufacturers recommend covered outdoor environments as opposed to full outdoor. UV RAYS are harmful to almost any man made material.
- •Limesite tiles and surfaces are not recommended for areas where the product will be submerged in water or liquid for a long period of time like ponds, pools and steam rooms The heat from fireplaces can discolour the sealer.
- •We do not recommend the tiles for inside a fireplace in direct contact with fire or if the heat around the fireplace is not deflected away from the wall.
- •Fireplace designs contributes to whether soot will form around it, this is not the norm and an indication of a poorly designed fireplace. Ideally the soot must go out throughout the Chimney/vent and the heat must push out away from the fireplace. Consult closely with us when unsure and want to keep your manufacturer warranty.