




KAVEL Recessed Round Lights

Simple, clean and efficient. Featuring evenly distributed lighting and made with top-notch materials for a long life span and excellent coverage of light.



KEY FEATURES

- Wide Illumination
- Hi-Purity Aluminium Reflector and Glass Cover
- Die Cast Aluminium

LIGHT SOURCE

Type	COB
Light Distribution	120D
CRI	80Ra / 90Ra
CCT	2700K, 4000K, 5000K

PHYSICAL ASPECTS

Luminaire Material	Aluminium
Finishing	White
Optics (Lens/Reflector)	Aluminium Reflector
Ingress Protection IP	IP44

ELECTRICAL SPECIFICATIONS

Input Voltage (V)	220-240VAC, 50/60Hz
Power Factor	0.9
THD	< 15%

UPGRADEABLE OPTIONS

Dimming - Phase Cut/1-10V
DALI Control
Emergency - Power Pack

Further engineering data is available upon request.

NAME	POWER	LUMENS	CUT-OUT SIZE	DIMENSIONS	PRODUCT CODE
KAVEL 15W	15W	1500	ø110	ø130 x 70	LSSC-DLKAVR01-0415
KAVEL 20W	20W	2000	ø145	ø165 x 70	LSSC-DLKAVR01-0620
KAVEL 30W	30W	3000	ø190	ø210 x 70	LSSC-DLKAVR01-0830