




### TUTTLINGEN Recessed Square, Single-Axis Light

A square spotlight with increased cutoff, featuring a single axis for better light positioning.



#### KEY FEATURES

- Contrasting colour luminaire creates uniqueness
- Slightly recessed for increased cutoff
- Wide Illumination with Hi-Purity Aluminium and Clear Glass

#### LIGHT SOURCE

|                    |                     |
|--------------------|---------------------|
| Type               | COB                 |
| Light Distribution | 120D                |
| CRI                | 80Ra / 90Ra         |
| CCT                | 2700K, 4000K, 5000K |

#### PHYSICAL ASPECTS

|                         |                     |
|-------------------------|---------------------|
| Luminaire Material      | Aluminium           |
| Finishing               | White               |
| Optics (Lens/Reflector) | Aluminium Reflector |
| Ingress Protection IP   | IP44                |

#### ELECTRICAL SPECIFICATIONS

|                   |                     |
|-------------------|---------------------|
| Input Voltage (V) | 220-240VAC, 50/60Hz |
| Power Factor      | 0.9                 |
| THD               | < 15%               |

#### UPGRADEABLE OPTIONS

Dimming - Phase Cut/1-10V  
DALI Control  
Emergency - Power Pack

Further engineering data is available upon request.

| NAME           | POWER | LUMENS | CUT-OUT SIZE | DIMENSIONS         | PRODUCT CODE      |
|----------------|-------|--------|--------------|--------------------|-------------------|
| TUTTLINGEN 8W  | 8W    | 800    | 100 x 100    | L115 x W115 x H84  | LSSC-SPTTG01-0308 |
| TUTTLINGEN 15W | 15W   | 1500   | 120 x 115    | L145 x W145 x H101 | LSSC-SPTTG01-0415 |
| TUTTLINGEN 25W | 25W   | 2500   | 140 x 135    | L170 x W170 x H115 | LSSC-SPTTG01-0525 |
| TUTTLINGEN 40W | 40W   | 4000   | 170 x 170    | L190 x W190 x H132 | LSSC-SPTTG01-0640 |