


ESCORT®



PASSPORT 9500ci International Quick Reference

9500ci

PASSPORT

INTERNATIONAL

▼ Power Button



▲ Programming Buttons ▲

Software Updates

PASSPORT's red light and speed camera database is easily updated using our exclusive detector software tools found on our web site. Firmware, or the operating software for the detector, can also be updated using these tools.

In order to have access to these updates, you must register your PASSPORT at www.EscortRadar.com. Once registered, you will receive email notifications that updates are now available for your database or firmware.

The PASSPORT 9500ci International will need to be powered up to use the software tools. If you have an Internet connected laptop computer, you can take it to the vehicle to download the updates.

There are 12 user-selectable options you can customize on your 9500ci. The buttons labeled VOL and BRT on the controller are used to enter Preferences. Once you enter Preferences, the VOL button is used to REVIEW your current choices, and BRT button is used to CHANGE settings.


How to use Preferences

- 1 To enter Preferences, press and hold both the VOL and BRT buttons down for 2 seconds.** The unit will display the word **Prefs**, accompanied by a voice announcement.
- 2 Press the VOL button to review the current settings.** You can either tap the button to change from item to item, or hold the button to scroll through the items.
- 3 Press the BRT button to change any setting.** You can either tap the button to change from setting to setting, or hold the button to scroll through all the options.
- 4 To exit Preferences, simply wait 8 seconds without pressing any button, or press the PWR button (⏻).** The unit will display **Complete**, accompanied by a voice announcement.



U L T I M A T E R A D A R • L A S E R D E F E N S E S Y S T E M

ESCORT®



DRIVE SMARTER.™

PASSPORT 9500ci International Quick Reference

Press the **VOL** button to go from one category to the next

Press the **BRT/CHG** button to change your setting within a category

▼
For descriptions and details of features and functions visit EscortRadar.com to view and download the complete PASSPORT 9500ci International Owner's Manual.

	PILOT (Power-on indication)	Pilot HWY Pilot H Pilot H.> Pilot U Pilot SPD	* Full word: Highway, AutoScn, etc. Letter: H, A, C, Cnx Letter, with scanning dot Vehicle voltage Vehicle speed
	CRUISE ALERT	OFF 20-100	* 20 KPH. Offers double beep alert tones below specified speed 20, 25, 30... 100 KPH
	GPS	GPS ON GPS OFF	* GPS On GPS Off
	AUTOLEARN	aLrn OFF aLrn ON	* AutoLearn Off AutoLearn On
	SPEED ALERT	sAlrt ON sAlrt OFF	* Speed Alert On Speed Alert Off
	METER	Meter STD Meter EXP Meter SPC	* Bar-graph Meter Expert Display Spec Display
	AUTOMUTE	aMute ON aMute OFF	* AutoMute On AutoMute Off
	UNITS	Units MET Units ENG	* Units Metric Units English
	VOICE	Voice ON Voice OFF	* Voice Alerts On Voice Alerts Off
	LANGUAGE	Lang ENG Lang SPA	* Language English Language Spanish
	BANDS	Bands DFT Bands MOD	* Factory Default Settings Factory Default Settings Modified
When KSW is off, each K segment can be turned on or off	K1 (23.950 - 24.110) ON or OFF (default is on) K2 (24.110 - 24.175) ON or OFF (default is on) K3 (24.175 - 24.250) ON or OFF (default is on)		Turn bands ON or OFF by pressing the MUTE button
When KaSW is off, each Ka segment can be turned on or off	Ka1 (33.388 - 33.708) ON or OFF (default is off) Ka2 (33.713 - 33.888) ON or OFF (default is off) Ka3 (33.888 - 34.208) ON or OFF (default is off) Ka4 (34.206 - 34.589) ON or OFF (default is on) Ka5 (34.588 - 34.804) ON or OFF (default is off) Ka6 (34.808 - 35.166) ON or OFF (default is off) Ka7 (35.166 - 35.388) ON or OFF (default is off) Ka8 (35.388 - 35.625) ON or OFF (default is on) Ka9 (35.628 - 35.848) ON or OFF (default is off) Ka10 (35.848 - 36.008) ON or OFF (default is off)	X ON or OFF (default is OFF) KSW ON or OFF (default is ON) KMTR ON or OFF (default is OFF) KaSW ON or OFF (default is OFF) POP ON or OFF (default is OFF) SWS ON or OFF (default is OFF) LSR RECV or SHFT or OFF (default is RECV) RDR ON or OFF (default is OFF)	* Factory Default Settings One or more bands have been changed
	MARKERS	Mark DFT Mark MOD rCam ON or OFF (default is ON) sCam ON or OFF (default is ON) aCam ON or OFF (default is ON) Trap ON or OFF (default is ON) Othr ON or OFF (default is ON)	* Factory Default Settings

* Factory Default Settings

Tuned Exclusively For The European Union