



G4 & G45 Burner Size Compatibility for Safety Valves

Valve Model	Gas Type	Max BTU [†] Input	G4 & G45 Standard	G45-2 See-thru
SPK-26	N.G.	100,000	12" - 36"	16" - 30"
SPK-26P	L.P.	200,000	12" - 60"	16" - 60"
APK-10	N.G.	230,000	12" - 60"	16" - 60"
APK-10P	L.P.	372,000	12" - 60"	16" - 60"
APK-11	N.G.	70,000	12" - 24"	16" - 18"
APK-11P	L.P.	110,000	12" - 42"	16" - 30"
APK-15	N.G.	85,000	12" - 24"	16" - 18"
APK-15P	L.P.	135,000	12" - 42"	16" - 36"
APK-17	N.G.	100,000	12" - 42"	16" - 30"
APK-17P	L.P.	200,000	12" - 60"	16" - 60"
EPK-1	N.G.	88,000	12" - 24"	16" - 18"
EPK-1P	L.P.	110,000	12" - 42"	16" - 30"
EPK-2	N.G.	120,000	12" - 30"	16" - 30"
EPK-2P	L.P.	190,000	12" - 60"	16" - 60"
EPK-2V-TR	N.G.	120,000	12" - 30"	16" - 30"
EPK-2VP-TR	L.P.	180,000	12" - 60"	16" - 60"
EPK-3V-TR	N.G.	200,000	12" - 60"	16" - 60"
EPK-3VP-TR	L.P.	320,000	12" - 60"	16" - 60"

[†] Using Real Fyre® Burner Systems