

Match Lighted/EIS Ready Hearth Kits

Propane requires safety control. See Pages 58-59 for Safety Lighting Controls.

Hearth Kits Includes: Pan Filler - Sand for Natural Gas (Indoors) or Volcanic Ash for Propane and Natural Gas (Outdoors), Ember Magic, Flexible SS Non-Whistling Connector Kit, Damper Clamp, Instructions.

NOTE: Burners for Vented Sets produce soot and other combustion products and are for use ONLY in fully functioning fireplaces in which it is safe to burn wood and with the damper wide open. Glass Doors must be wide open when burning for proper ventilation, proper combustion and cooling of safety control valves and components.

For Outdoor Use (Natural Gas): Suffix Item # with "OS" and indicate "Outdoor use" in your purchase order description and we will send Volcanic Ash in place of Sand, which we recommend to achieve an even flame in outdoor use. ****Match Lighted only - Controls are not warranted for outdoors.**

Set Size	Item #	Minimum Footprint Dimensions		Ctns	Wt	Certif.	BTU/hr
		To Center	Assembly in FireBox				(NG / LP)

Custom Pan Burner with Strap Legs, 12" deep For Single, Double and Multi-Sided Fireplaces
Black Painted Steel Add N for Natural Gas; P for Propane after Item # [Not for use with a Grate]

12, 15, 16	CS16-B-	22" front / 17" rear / 14" depth	1	25	RIW	65k / 27k
18	CS18-B-	24" front / 19" rear / 14" depth	1	28	RIW	75k / 27k
20, 21	CS21-B-	27" front / 22" rear / 14" depth	1	32	RIW	76k / 35k
24	CS24-B-	30" front / 25" rear / 14" depth	1	36	RIW	90k / 37k
27, 30	CS30-B-	36" front / 31" rear / 14" depth	1	47	RIW	110k / 50k

Custom Pan Burner with Strap Legs, 16" deep For Single, Double and Multi-Sided Fireplaces
Black Painted Steel Add N for Natural Gas; P for Propane after Item # [Not for use with a Grate]

24, 27	CS27W-B-	33" front / 28" rear / 18" depth	1	56	RIW	100k / 60k
27, 30	CS30W-B-	36" front / 31" rear / 18" depth	2	60	RIW	120k / 70k
30, 33	CS33W-B-	39" front / 34" rear / 18" depth	2	70	RIW	130k / 75k
36	CS36-B-	42" front / 37" rear / 18" depth	2	74	RIW	140k / 85k
42	CS42-B-	48" front / 43" rear / 18" depth	2	81	RIW	150k / 95k
48	CS48-B-	54" front / 49" rear / 18" depth	2	98	RIW	175k / 105k
54	CS54-B-	60" front / 55" rear / 18" depth	2	110	RIW	215k / 145k
60	CS60-B-	66" front / 61" rear / 18" depth	2	120	RIW	225k / 185k

Manual "EASY" Safety Pilot Control – Factory Installed

Manual Control with Standing Pilot – turn the knob to light the main burner.

Includes: Pan Filler, Ember Magic, Flexible SS Non-Whistling Connector Kit,
Damper Clamp, Instructions.

Manual "EASY" Controls may be upgraded at any time to either "Remote Ready" or "Variable Flame Height Remote Control" functionality with the addition of either the **SE-UP1** or **RE-UP1** upgrade kits.
(See top of Page 59)

NOTE: Burners for Vented Sets produce soot and other combustion products and are for use ONLY in fully functioning fireplaces in which it is safe to burn wood and with the damper wide open. Glass Doors must be wide open when burning for proper ventilation, proper combustion and cooling of safety control valves and components.

NOTE: Any item listed in this section may be equipped with the SPK1 (manual safety standing pilot control with better flame height modulation than SPK3E "EASY" control, but not upgradable to Remote functionality).

• Replace "SPK3E" or "ME" with "SPK1" in Item #. • Same Price as listed for SPK3E or ME.

Standard Connection is on the Right Side. You may specify "Left Side Feed" when ordering if you wish to have the connection on the Left Side.

Standing Pilot Control System		Minimum Footprint Dimensions			BTU/hr	
Set Size	Item #	To Center Assembly in FireBox	Ctns	Wt	Certif.	(NG / LP)

Custom Pan Burner with Strap Legs, 12" deep (16" for 27W and 30W)

Black Painted Steel For Single, Double and Multi-Sided Fireplaces

Add N for Natural Gas; P for Propane after Item #

[Not for use with a Grate]

12, 15, 16	CS16-B-SPK3E-	28" front / 20" rear / 14" depth	1	27	RIW	65k / 27k
18	CS18-B-SPK3E-	30" front / 22" rear / 14" depth	1	30	RIW	75k / 27k
20, 21	CS21-B-SPK3E-	33" front / 25" rear / 14" depth	1	38	RIW	76k / 35k
24	CS24-B-SPK3E-	36" front / 28" rear / 14" depth	1	42	RIW	90k / 37k
24, 27	CS27W-B-SPK3E-	39" front / 31" rear / 18" depth	1	58	RIW	100k / 60k
27, 30	CS30-B-SPK3E-	42" front / 34" rear / 14" depth	1	49	RIW	110k / 50k
27, 30	CS30W-B-SPK3E-	42" front / 34" rear / 18" depth	2	62	RIW	120k / 70k

Custom Pan Burner with Round Legs, 12" deep (16" for 27W and 30W)

Stainless Steel For Single, Double and Multi-Sided Fireplaces

Add N for Natural Gas; P for Propane after Item #

[Not for use with a Grate]

12, 15, 16	CS16-SR-SPK3E-	28" front / 20" rear / 14" depth	1	27	RIW	65k / 27k
18	CS18-SR-SPK3E-	30" front / 22" rear / 14" depth	1	30	RIW	75k / 27k
20, 21	CS21-SR-SPK3E-	33" front / 25" rear / 14" depth	1	38	RIW	76k / 35k
24	CS24-SR-SPK3E-	36" front / 28" rear / 14" depth	1	42	RIW	90k / 37k
24, 27	CS27W-SR-SPK3E-	39" front / 31" rear / 18" depth	1	58	RIW	100k / 60k
27, 30	CS30-SR-SPK3E-	42" front / 34" rear / 14" depth	1	49	RIW	110k / 50k
27, 30	CS30W-SR-SPK3E-	42" front / 34" rear / 18" depth	2	62	RIW	120k / 70k

Remote Ready "EASY" Safety Control –Factory Assembled

Standing Pilot Control System

Latching solenoid system that controls the ON/OFF of the burner(s) with the receiver switch or one of five Wireless Remote Transmitter Devices (sold separately – see bottom of Page 15):

- Wireless Hand-Held Remote Control with Simple ON/OFF (SR-2R) or Thermostat feature (THR-2R).
- Wireless Wall Timer (WT-2R) •Wireless Wall Switch (WS-2R) •Wireless Wall Thermostat (TS-2R)

"RPK3E" and "SE" are not "millivolt" systems. The Latching Solenoid is powered by 4-AA Batteries. Adjust the flame height manually by adjusting the knob at the valve (minimal adjustment available).

NOTE: Burners for Vented Sets produce soot and other combustion products and are for use ONLY in fully functioning fireplaces in which it is safe to burn wood and with the damper wide open. Glass Doors must be wide open when burning for proper ventilation, proper combustion and cooling of safety control valves and components.

Standard Connection is on the Right Side. You may specify "Left Side Feed" when ordering if you wish to have the connection on the Left Side.

Standing Pilot Control System		Minimum Footprint Dimensions			BTU/hr	
Set Size	Item #	To Center Assembly in FireBox	Ctns	Wt	Certif.	(NG / LP)

Custom Pan Burner with Strap Legs, 12" deep (16" for 27W & 30W)

Black Painted Steel For Single, Double and Multi-Sided Fireplaces

Add N for Natural Gas; P for Propane after Item #

[Not for use with a Grate]

12, 15, 16	CS16-B-RPK3E-	28" front / 20" rear / 14" depth	1	28	RIW	65k / 27k
18	CS18-B-RPK3E-	30" front / 22" rear / 14" depth	1	31	RIW	75k / 27k
20, 21	CS21-B-RPK3E-	33" front / 25" rear / 14" depth	1	39	RIW	76k / 35k
24	CS24-B-RPK3E-	36" front / 28" rear / 14" depth	1	43	RIW	90k / 37k
24, 27	CS27W-B-RPK3E-	39" front / 31" rear / 18" depth	1	59	RIW	100k / 60k
27, 30	CS30-B-RPK3E-	42" front / 34" rear / 14" depth	1	50	RIW	110k / 50k
27, 30	CS30W-B-RPK3E-	42" front / 34" rear / 18" depth	2	63	RIW	120k / 70k

Variable Remote "EASY" Safety Control - Factory Assembled

Standing Pilot Control System

Light the burner and control the flame height with the hand-held wireless remote control.
Includes: Pan Filler, Ember Magic, Flexible SS Non-Whistling Connector Kit, Damper Clamp, Instructions, Remote Transmitter.

NOTE: Burners for Vented Sets produce soot and other combustion products and are for use ONLY in fully functioning fireplaces in which it is safe to burn wood and with the damper wide open. Glass Doors must be wide open when burning for proper ventilation, proper combustion and cooling of safety control valves and components.

Please Note:
RMC1E and RE include the Hand-held Remote Transmitter.
RH2 or RH3 recommended to protect receiver from heat.

Standard Connection is on the Right Side. You may specify "Left Side Feed" when ordering if you wish to have the connection on the Left Side.

Standing Pilot Control System		Minimum Footprint Dimensions				BTU/hr	
Set Size	Item #	To Center Assembly in FireBox	Ctns	Wt	Certif.	(NG / LP)	

Custom Pan Burner with Strap Legs, 12" deep (16" for 27W and 30W)

Black Painted Steel For Single, Double and Multi-Sided Fireplaces

Add N for Natural Gas; P for Propane after Item #

[Not for use with a Grate]

12,15,16	CS16-B-RMC1E-	28" front / 20" rear / 14" depth	1	28	RIW	65k / 27k	
18	CS18-B-RMC1E-	30" front / 22" rear / 14" depth	1	31	RIW	75k / 27k	
20, 21	CS21-B-RMC1E-	33" front / 25" rear / 14" depth	1	39	RIW	76k / 35k	
24	CS24-B-RMC1E-	36" front / 28" rear / 14" depth	1	43	RIW	90k / 37k	
24, 27	CS27W-B-RMC1E-	39" front / 31" rear / 18" depth	1	59	RIW	100k / 60k	
27, 30	CS30-B-RMC1E-	42" front / 34" rear / 14" depth	1	50	RIW	110k / 50k	
27, 30	CS30W-B-RMC1E-	42" front / 34" rear / 18" depth	2	63	RIW	120k / 70k	