Variable Remote Electronic Ignition with Valve Vanisher

EIS Pilot-on-Demand System

Raises log set 2 5/8" above the floor.

Factory assembled Chassis/Burner/Control System. **Right side gas feed only.**Includes: Remote Transmitter, Pan Filler, Ember Magic,

Flexible SS Non-Whistling Connector Kit, Damper Clamp, Instructions.

NOTE: Burners for Vented Sets produce soot and other combustion products and are for use ONLY in fully functioning fireplaces in which it is safe to burn wood and with the damper wide open.

Glass Doors must be wide open when burning for proper ventilation, proper combustion and cooling of safety control valves and components.

EIS Pilot-	on-Demand Systen	Minimum Footprint Dimensions				BTU/hr
Set Size	Item #	To Center Assembly in FireBox	Ctns	Wt	Certif.	(NG / LP)

Custom Pan Burner, 12" deep (16" for 27W and 30W)

Black Painted Steel For Single, Double and Multi-Sided Fireplaces

Add N for Natural Gas; P for Propane after Item # [Not for use with a Grate]

15, 16	CS16-BR-VEI-	20" front / 20" rear / 14" depth	2	34	RIW	65k / 27k
18	CS18-BR-VEI-	22" front / 22" rear / 14" depth	2	37	RIW	75k / 27k
20, 21	CS21-BR-VEI-	26" front / 26" rear / 14" depth	2	43	RIW	75k / 35k
24	CS24-BR-VEI-	28" front / 28" rear / 14" depth	2	47	RIW	90k / 37k
27, 30	CS27W-BR-VEI-	31" front / 31" rear / 18" depth	2	65	RIW	110k / 60k
27, 30	CS30-BR-VEI-	34" front / 34" rear / 14" depth	2	60	RIW	100k / 50k
27, 30	CS30W-BR-VEI-	34" front / 34" rear / 18" depth	2	70	RIW	120k / 70k