

The high specification non-corrosive fittings have a high ingress protection from moisture, dust, corrosion and vandalism, offering a safer, more efficient alternative to festoon lighting.





1 x 36W
1 x 58W

IP65

Specification

- Voltage:** 110V
Wattage: 1 x 36W, 1 x 58W
Lamp (not included): T8 fluorescent tubes
Lumen Output: 2500 - 5000lm
Guarantee: 1 year
IP Rating: IP65
Material: Body made of high impact resistant ABS c/w clear polycarbonate diffuser
- Working Temp:** -20°C - 60°C
Extra Info: c/w plastic clips - stainless steel, clips available separately.



High frequency, low power factor ballast.
 Standards: F Mark, CE, BS EN60598-2-1 & BS EN60598-2-22.
 3 hour back-up emergency available.
 Supplied with suspension eye.
 Fittings can be supplied pre-wired with specified lengths of cable and junction box, coupler etc. Please request further information.

MODEL	WATTAGE	LUMEN OUTPUT	EMERGENCY	DIMENSIONS (L x W x D mm)
WF36SV	1 x 36W	2500lm	NO	1270 x 98 x 102mm
WF58SV	1 x 58W	5000lm	NO	1586 x 98 x 102mm
EFW58SV	1 x 58W	5000lm	YES	1586 x 98 x 102mm

Specification Sheet - 110V Non Corrosive Site Light