

CAPACITY

3000 lbs.

INTEGRAL BATTERY / CHARGER

(2) 12V 85AH maintenance free batteries with 110VAC 15A plug-in automatic charger.

SPEED

24-volt Curtis travel controller with infinitely variable speed control.

Variable from 0 mph to 2.8 mph empty Variable from 0 mph to 2.5 mph loaded

WEIGHT

450 lbs. with battery and charger (27x45 Standard)

TIRES / WHEELS

DRIVE

8.3" x 2.8" polyurethane LOAD

(2) 2.9" x 3.5" polyurethane

TILLER ARM CONTROLS

Travel, lift, and lower functions are located in the ergonomic operator handle. All operator controls are accessible without having to lift the hand from the handle.

Angle grips are designed to allow easy operation with either hand. Wrap around guard, reversing switch, thumb control. and horn are standard. Low mounted tiller arm offers excellent operator comfort and minimum steering effort.

ELECTRICAL

Electric braking, quick disconnect EPD power cut off and battery discharge indicator are standard equipment.

HYDRAULICS

Permanent magnet pump motor and chrome plated lift cylinder provide smooth lifting & lowering. Pump includes DC motor, solenoid, and gear pump.

DRIVE

24-Volt brushless DC drive motor efficiency and delivers up to 4 hours of continuous duty cycle on a single charge.

BRAKES

Electromagnetic disc brake.

SERVICEABILITY

E30

Electric

Pallet Jack

UPGRADE YOUR HAND PALLET TRUCK. NO MORE PUSHING.

PULLING OR PUMPING

Removable one piece power head cover allows for easy maintenance.

BATTERY UPGRADE OPTION


· 85AH (AGM) batteries for extended run times up to 6 hours


AVAILABLE FORK SIZES

- 27x45 Standard
- 27x36, 27x42, 27 x 48, 22 x 36, 22 x 42, 22 x 48

AVAILABLE TRUCK OPTIONS

- Load back rest, 48" or 60" high
- Tool tray with load restraint





 $\begin{tabular}{ll} \textbf{Certification} \\ \textbf{All units are built to be in compliance with the Occupational Safety \& Health Act (OSHA)} \\ \end{tabular}$

