



PUMP IT, GROUT IT, SPRAY IT

The Pump Catalog From IMER USA





IMER USA West
Assembly Facility
Hayward, CA



IMER USA
Headquarters & Assembly Facility
Capitol Heights, MD

Table of contents

A Brand for Total Strategy	3
Quality & Services	
Screw Pumps	5
Koine 35	
Koine 4	
Small 50	
Step-Up 120	
Silent 300 Prestige	
Accessories & spare parts	
Compressor	
Mixing	14
Mix 120 Plus	
Concrete Pump	23
Booster 15	
Booster 15 setups	
Concrete Accessories	
Machinery Application Chart	44

Electric Motors Available

115V/60Hz 1 phase

220V/60HZ 1 phase

220V/60HZ 3 phase

Worldwide Development and Distribution



Batch Plants
Basaldella di Campoformido (Udine), Italy



Earth Moving
San Gimignano (Siena), Italy



Truck Mixers
Aksaray, Turkey



Aerial Lifts
Pegognaga (Mantua), Italy



Group HeadquartersPoggibonsi (Siena), Italy



Pumps, Saws, Mixers & Hoists Rapolano Terme (Siena), Italy

With the strength of over 550 employees, the Group has 5 production plants, which occupy a total surface area of over 96 acres with 900,000 SF under one roof.

The IMER Group brand boasts a very complete range of construction equipment whoih allow the contractor to work better, safer and more efficiently.

Since 1967, market and export trends pushed the Company to expand into foreign markets, setting up foreign sales and distribution.

At present there are nine branches in Europe, the United States, Asia and Africa.

A further force behind the Group's expansion is the presence in the major rental centers around the world. While in Italy a network of over 1000 dealers ensures widespread market coverage.



IMER Access Pegognaga (Mantua), Italy

e Officine Riunite - Udine

Basaldella di Campoformido (Udine), Italy

HIMER

San Gimignano (Siena), Italy

IMER - L&T

Aksaray, Turkey



HEADQUARTERS

Poggibonsi (Siena), Italy



Quality Control and Customer Service



High quality materials and products



Years of experience and technological innovation



Service support is available for all



Products and services on the web at www.imerusa.com





KOINE SERIES CONTINUOUS PUMPS

for premixed mortars and grouts



Single-phase mortar & plaster sprayer for bagged premixed materials

<76 dB

KOINE 35 220V/60Hz

5 HP 1 Phase

Model # 1106006

MULTIPLE APPLICATIONS

For the continuous mixing, spraying and pumping of pre-blended cementitious and gypsum based mortars, stucco, fireproofing, self-leveling underlayments and grouts.

Mixing chamber access is quick and easy. Clean up at the days end is simple.

Use the standard water booster pump to quickly and easily flush out the material hose

Continuous operation means that production is very efficient and effective. Run fast... run hard!

Onboard dual diaphragm compressor delivers a constant flow of air for spray applications

CONTROL PANEL



- 2 Current indicator light
- 3 ON/OFF switch
- 4 Emergency stop button
- 5 Manual water control
- 6 Water booster pump switch
- 7 Min. water pressure indicator
- 8 Mixing chamber safety sensor
- 9 Forward / Reverse
- 10 Rotor / stator speed control

The sophisticated inverter control panel monitors the incoming electricity and the output power to the motors. The LED display lets you know how the pump is running and reports any problems



Continuous production, break a bag and get going...Automatically!



Standard Equipment

- Continuous mixer
- ✓ D8 1.5 stator and rotor
- Material delivery pressure gauge
- ✓ Control panel with exclusive IMER 4 speed inverter
- ✓ Self-priming water booster pump
- ✓ Water system with flow meter and NOFREEZE discharge valve
- √ 66' of electric cord
- √ 66' of water hose Ø 19 mm (3/4")
- √ 50' of air hose Ø 13 mm (9/16")
- √ 50' of material hose Ø 25 mm (1")
- Spray gun with nozzles
- ✓ Hose cleaning kit with toolbox
- Mixing chamber clean out tool



Fire-proofing and stucco setup

?	

- ✓ 1107085 Rotor Eco Star
- ✓ 1107517 Turbo Mixer (use with 1107028 and 1107029)
- √ 1107028 D8 1.5 stator
- ✓ 1107029 D8 1.5 rotor w/tab (for use with Turbo Mixer)

Self-leveling and grouting setup

- ✓ 1107517 Turbo Mixer (use with 1107028 and 1107029)
- ✓ 1107028 D8 1.5 stator
- ✓ 1107029 D8 1.5 rotor w/tab
- √ 1107597 Self-leveling mixing paddle

Power	-	220V/60Hz, 1 phase
Total machine horsepower	HP	5
Drive motor	HP	3
Feeding impeller motor	HP	1/2
Electric compressor	-	1HP, 9 CFM
Material flow rate (D8 - 1.5 stator)	CF/h	34, 45, 53, 60
Maximum pumping distance*	Ft.	300'
Gearbox speed	RPM	180, 240, 280, 320
Water booster pump	HP/PSI	1/2hp /70 PSI boost
Dimensions width/length/height	ln.	27/62/47
Weight	Lbs.	561
Sound level	dB(A)	< 76 very quiet!

(*) NOTE The pumping distance may vary depending on: the type of material used, pumping height, material consistency, type of pump installed.

Hi speed continuous mixing / pumping for bagged premixed materials




MULTIPLE APPLICATIONS

When the application calls for more volume, more distance and more hours of operation...upgrade to the Koine 4, 220V, 3 phase.



The heavy duty 7.5 HP, 3 phase electric motor with a gearbox drive reduction system delivers 100% duty cycle for continuous use all day long

Comes standard with R8 stator, 21 GPM of flow or 7 qty, 50 lb. bags of grout per minute.





Self-priming water booster pump with stainless steel housing and brass impeller. A reliable and long lasting design

Continuous production, break a bag and get going...Automatically!

CONTINUOUS FEED IMPELLER

Standard Equipment

- Stator and rotor R8
- ✓ Material delivery pressure gauge
- ✓ Gear driven feed impeller
- ✓ Vacuum ready kit for controlling dust
- ✓ Self-priming stainless steel water pump
- ✓ Water system with flow meter and NOFREEZE discharge valve
- ✓ 130' electric cord
- √ 130' water hose Ø 19 mm (3/4")
- ✓ 33' material hose, Ø 35 mm (1-3/8") with quick connects
- ✓ 90' of wired remote control to start and stop the pump
- ✓ Tool box w/ gun & accessories
- Clean up kit (scraper and sponge)
- ✓ Turbo mixer kit for additional mixing for lump free discharge










TURBO KIT AT NO CHARGE!



Turbo mixer gives a little extra mixing to the material before entering the hose

When needed the mixing chamber and the compressor can be removed quickly in order to make it even easier to move the Koine 4 from place to place

Store all your accessories in this handy tool box. Never lose pieces



CONTROL PANEL



- 1 ON/OFF switch
- 2 Emergency stop button
- 3 Stator/rotor control
- Manual water output switch
- 5 Feeding blade ON/OFF
- 6 Water pump ON/OFF
- Electrical current indicator
- 8 Emergency stop light
- 9 Water pressure indicator
- 10 Emergency reverse switch

Fire-proofing and stucco set-up

- ✓ 1107028 Stator D8 1.5 Yellow 75 CF/h
- ✓ 1107029 Rotor with tab D8 1.5 ECO
- ✓ 1107005 Koine gun kit for fireproofing and stucco
- 3 Phase Dual Diaphragm Compressor
- ✓ 1107549 5' Overhead gun
- ✓ 1107565 35mm 25mm camlock reducer
- ✓ 1107103 25mm Geka coupling clean out kit
- √ 1107519 25mm cleaning balls

Self-levelling underlayment set-up

✓ 1107528 Additional length of 35mm x 33' hoses

1	V V V V	
	Koine	0

Power	-	220V/60Hz, 3 Phase
Total machine power	HP	9
Drive motor power	HP	7.5
Feeding impeller motor	HP	1
Water booster pump	HP/PSI	1/70 PSI boost
Material flow rate	CF/h	169
Max. pumping distance with Ø 25 mm (1") hose	Ft.	200+
Max. pumping distance with Ø 35 mm (1-3/8") hose	Ft.	300+
Gearbox speed	RPM	400
Loading height	ln.	35.5
Dimensions width/length/height	ln.	29/47/61.5
Weight	Lbs.	475
Sound level, very quiet!	dB (A)	< 65

^(*) NOTE The pumping distance may vary depending on: the type of material used, pumping height, material consistency, type of pump installed



MIGHTY SMALL 50

premixed and conventional mortars and grouts for pumping and spraying



Screw pump for pumping and spraying applications

APPLICATIONS

For pumping and spraying of conventional mortars and grouts, waterproofing products, coatings, stucco, tuck-pointing, self-leveling underlayments, fireproofing and various other cementitious and acrylic products.

SMALL 50 115V/60Hz 2 HP, 1 Phase Model # 1106045

Optional 9 CFM compressor, drops in and lifts off





CONTROL PANEL

screen and air compressor.



- 1 On/Off switch
- 2 Rotor/stator speed control
- 3 Emergency stop button
- 4 Vibrating grate switch
- 5 Rotor/stator forward/reverse
- 6 Safety default light
- 7 Current supply light
- 8 Diagnostic display

Standard Equipment SMALL 50

- ✓ Stainless steel hopper
- ✓ Rotor and stator D8 1.5 ECO versatile performance
- ✓ Inverter driven control panel
- ✓ Electric remote control cable
- ✓ Pressure gauge for material pressure
- ✓ Accessory tool box

Power supply	-	120V/60Hz
Pump motor	HP	1.75
Material flow rate	CF/h	1.7 - 30
Max. aggregate size	ln.	1/4
Maximum pumping distance hose Ø 19 mm (3/4")*	Ft.	100
Maximum pumping distance hose Ø 25 mm (1")*	Ft.	150
Hopper capacity	CF	1.75
Loading height	ln.	25.5
Dimensions W x L x H	ln.	20.5/44/25.5
Weight (with compressor)	Lbs.	90 (152)
Sound pressure level	dB (A)	< 74

upon stopping to reduce the

pressure in the hose and gun

(*) NOTE The pumping distance may vary depending on: the type of material used, pumping height, material consistency, type of pump installed



Add accessories to fit your needs. Call IMER USA at 800-275-5463 to discuss your requirements.



SMALL 50 CONFIGURATIONS

			P	umping and spray	ing applications
	Pumping of grouts, self-leveling underlayments	Spraying fireproofing, repair mortar, stucco base coat 1/8" or more of build-up	Spraying waterproofing, acyrlic stucco, elastomeric coatings 1/8" or less of build-up	Controlled pressure grout injection with pressure regulator 0 - 65 PSI	Tuck-pointing and grouting
Dual diaghram compressor		•	•		
Mortar, stucco and fireproofing gun kit		•			
Stucco, paint and fine coatings gun kit			•		
Grout injection kit				•	
Tuck point gun kit					•
25mm (1") material hose	•				
5' overhead wand		0			
Vibrating hopper				0	0
Vibrating screen	0	0	0		
Pipe hook	0				



MORTARMAN 120+

premixed materials, mortars, stucco, grouts



MORTARMAN 120 Plus

Portable vertical shaft mixer

APPLICATIONS

Ideal for mixing bagged premixed materials, dry-pack, fireproofing and cements with aggregates up to 3/8", pea gravel is no problem





Standard Equipment

- Low voltage switch
- ✓ Electric safety limit switch for drum
- ✓ Bag splitters on the drum grate
- Extendable handles
- Additional wheels
- Lifting hooks

Orum capacity	CF	4.5
Batch output	CF	3
Drum diameter	ln.	30
Max aggregate size	ln.	3/8
Paddle speed	rpm	38
Electric motor power rate 110V/60Hz	HP	2
Current draw	Α	15
SPL in operator's position	dB(A)	70
Machine weight (packing)	Lbs.	286 (310)
Dimensions I/h/w (packing)	ln.	33/50/30 (35/38/31)



The paddles are always in the mix, working hard. Even stiff muds are mixed thoroughly and completely.



Step-Up 120

premixed materials, mortars, stucco, grouts



Hi-production screw pump for self-levelling and grouts

APPLICATIONS

For pumping gypsum or cement based self-levelling screeds, non-shrink grouts and repair mortars.





- 1 On/Off switch
- 2 Current supply light
- 3 Emergency stop button
- 4 Rotor/stator forward/reverse
- 5 Vibrating grate switch
- 6 Safety default light

Grouts or self-consolidating concretes - 3/8"

√ 1107149 IM25L rotor/stator kit with mounting hardware



Self-levelling and fine grouts

✓ 1107533 Additional length of 50mm (2") x 33' hoses

Standard Equipment

- Three-phase 220V/60Hz motor 10 HP
- Electric control panel
- Built-in low voltage electric remote control with 120' of cable
- ✓ 66' three phase power supply cord
- 60.12 high performance rotor-stator
- Vibrating grid
- 100' of hose (3 x 33') Ø 50 mm (2")
- Accessory box

Power	-	220V/60Hz, 3 phase
Motor power rating	HP	10
Max aggregate size std. rotor - stator	ln.	5/16"
Flow rate	CY/h	9.5
Max pumping distance	Ft.	200
Max pumping height	Ft.	100
Hopper capacity	CF	4.25
Dimensions length/width/height	ln.	91/32/38
Weight	Lbs.	616
Sound pressure level	dB (A)	< 79

^{*} The pumping distance may vary depending on: the type of material used, pumping height, material consistency, type of pump installed.

'EP-UP

Screw pump for pumping and spraying applications

APPLICATIONS

For spraying and pumping conventional mortar and premixed cements. fibre-reinforced cements, grouts, fireproof materials, self-levelling underlayments and waterproofing products.







CONTROL PANEL


Single-phase version 220V/60Hz



- 1 On/Off switch
- 2 Rotor/stator speed control
- 3 Emergency stop button
- 4 Vibrating grate switch
- 5 Rotor/stator forward/ reverse
- Safety default light
- 7 Current supply light
- 8 Diagnostic display

CONTROL PANEL

Three-phase version 220/60Hz



- 1 On/Off switch
- 2 Current supply light
- 3 Emergency stop button
- 4 Rotor/stator forward/ reverse
- 5 Vibrating grate switch
- 6 Safety default light
- Speed control switch

Standard Equipment # 1106090 230V/60Hz, single phase

- Electric panel with inverter
- ✓ IM25L rotor and stator
- ✓ Spray gun for conventional/premixed mortar
- ✓ Vibrating grate
- 9 CFM compressor
- ✓ 66' single phase power cord
- ✓ 100' (3x33) of material hose Ø 35 mm (1-3/8") with cam couplings
- ✓ 100' of air hose Ø 13 mm (9/16") with quick couplings
- Accessory box for conventional mortar spraying

Standard Equipment Part # 1106091 230/60Hz, 3 phase

- ✓ Electric panel with low and high speed
- ✓ IM25L rotor and stator up to 3/8" aggregate
- ✓ Spray gun for conventional/premixed mortar
- ✓ Vibrating grate
- 11 CFM compressor
- ✓ 66' three phase power cord
- √ 100' (3x33) of mat. hose Ø 35 mm (1-3/8") with cam couplings
- ✓ 100' of air hose Ø 13 mm (9/16") with quick couplings
- Accessory box for conventional mortar spraying





COMPRESSOR




The dual diaphragm "V" stroke compressor provides ample air for spray applications – Continuous duty rated and maintenence free.

Hopper drain plug for easy clean out of materials



MIX COMPLETELY AND QUICKLY



The planetary mixing action of the vertical shaft mixer reduces mixing time to 2 minutes. The 3 cubic feet of output discharge directly into the hopper.

Torsion bar suspension for safe and smooth road towing

Complete with tail light package for safe towing

		STEP-UP 120 1 Phase	STEP-UP 120 3 Phase
Power	-	220V, 60Hz, single phase	220V, 60Hz, three phase
Motor power rating	HP	3	7.5
Mixer power rating	HP	2	2
Electric compressor	-	1 HP / 9 CFM	2 HP / 11 CFM
Max aggregate size (IM 25L)	ln.	5/16	3/8
Maximum flow rate	CY/h	2	1.35/2.75
Horizontal pumping distance (*)	Ft.	200	200
Vertical pumping distance (*)	Ft.	100	100
Hopper capacity	CF	4.25	4.25
Mixer capacity	CF	4.25	4.25
Dimensions W x L x H	ln.	32/80/50	32/80/50
Weight	Lbs.	888	900

(*) The pumping distance may vary depending on: the type of material used, pumping height, material consistency, type of pump installed.



Silent 300 Prestige

premixed materials, mortars, stucco, grouts



SILENT 300 PRESTIGE

Diesel powered screw pump for pumping and spraying

APPLICATIONS

For mixing, pumping and spraying of mortars in bags or from silo: premixed materials, cement or gypsum based premixed materials, fireproofing, grouts, epoxies, selfleveling underlayments or repair mortars.



Safety sensor system stops the mixing paddles if the grid is opened

All the drive systems are hydraulic, very safe and very little maintenance

Comes standard with adjustable 2L6 rotor / stator. Other stator options available



The high shear and high capacity mixer (6.3 CF) with hydraulic drive is powerful and reliable. Materials are ready to go in no time



Adjusts engine RPMs according to power demands

IMER's mixer paddles aggressively mix the material, this ensures a clump free mud in the shortest time possible





Standard Equipment

- ✓ Kohler Focs 1003/3 cyl. diesel engine
- √ 14 CF/m compressor
- ✓ 2L6 screw pump
- √ 3 x 33' material hose Ø 35 mm (1-3/8")
- 100' wired remote control
- ✓ 2 clean-out sponges
- √ 53' + 66' air hose Ø 13 mm (9/16")
- ✓ Programable mixer timer
- ✓ 6.3 CF Hydraulic dump mixer
- Hydraulic variable speed pump
- Hyrdraulic pressure washer
- Metal accessory box



OPTIONAL ELECTRONIC WATER METER



Part # 1107209
AQUA CONTROL electronic water meter for quick and easy addition of metered water into the mixer every batch.

DIESEL MOTOR



3-cylinder, liquid-cooled diesel engine that meets the latest EPA regulations. 2400 rpm operating speed for less wear and low fuel consumption.

STANDARD PRESSURE WASHER



Part # 1107208 2,000 PSI pressure washer cleans very effectively with minimal blow-back.

CONTROL PANEL



Anti-vibration control panel with electromechanical controls and standard hour meter

Traditional & premixed mortar

√ 1107036 - Vibrating screen
√ 1107149 - Pumping Unit IM25L

✓ 1107149 - Pumping Unit IM25L (for course aggregate)
 ✓ 1107577 - Spray gun for traditional & premixed mortar

✓ 1107560 - 5-piece kit up to Ø 16 mm (5/8")

Self-levelling floor screeds and grouts

- ✓ 1107090 Pumping Unit 60.12 for self-levelling underlayments
- ✓ 1107149 Pumping Unit IM25L for 3/8" aggregates up to 35%
- ✓ 1107036 Vibrating grate for screening larger than 3/8"

Motor power rate ISO 3046/1-IFN	HP	20
Compressor flow rate	CF/m	14
Max pumpable aggregate size	ln.	1/4 (2L6)
Variable flow rate	CY/h	0 - 4.5 (2L6)
Max pressure	PSI	580 (2L6)
Hopper capacity	CF	7
Mixer capacity	CF	6.3
Dimensions length/width/height (mixer tilted)	ln.	131.5/53.5/53
Weight	Lbs.	1,653
Sound pressure level	dB (A)	< 78

^(*) The road towing is valid only in the countries where it is allowed.



Booster 15

Concrete and shotcrete



2-cylinder piston pump with "S"- Valve technology

APPLICATIONS

For pumping concrete, shotcreting and high strength grouts





Wireless remote control precisely delivers material where you need it.

Compact dimensions, easy on-site transport and better handling



Surge brakes give you extra stopping power while towing

CONTROL PANEL



Antivibration panel with electromechanical controls

Standard Equipment

- √ 4-cylinder liquid cooled Diesel engine, Kohler FOCS 35 HP
- Concrete hopper with agitator
- ✓ Grid with 12V vibrator
- Hydraulic system with reversing
- ✓ Pumping unit with S-valve for automatic compensation of clearance and wear
- √ 4" Heavy Duty delivery manifold (Ø 4")
- ✓ Control panel with electromechanical controls
- ✓ Four-function remote control via cable
- ✓ Piston head installation and extraction tool kit
- ✓ Complete with heavy duty highway tow package
- ✓ Accessory box
- ✓ Auto-greasing system



Electronic proximity sensors control the S-valve and piston action

Auto-greasing system provides continuous lubrication to the vital components

2-cylinder piston pump (4"), hydraulicly driven.



Long lasting removable rear light panel

Torsion bar suspension for smooth towing in any condition

Diesel engine	-	Kohler FOCS 4 cil. Mod. 1404
Installed power rate	HP	35
Pumping system	-	Two-cylinder with hydraulic control
Max aggregate size	ln.	1"
Flow rate (*)	CY/h	3-20
Pumping pressure (*)	PSI	1,000
Pipe outlet	-	Heavy Duty 4"
Hopper capacity	CF	7
Loading height	ln.	42.5
Dimensions length/width/height	ln.	156/57/60
Weight	Lbs.	3,100

*NOTE The max flow rate and the max pumping pressure cannot be performed at the same time.

BOOSTER 15

2-cylinder piston pump with "S"- Valve

DRIVE SYSTEM



COOL FAST
large-sized
cooling system
for use in
extreme
conditions

Pump with exclusive SOFT SPRITZ injection system when shotcreting applications Engines that meet the latest EPA regulations. Well soundproofed engine compartment

HOPPER



S-valve with self-sealing collar automatically compensates for S-valve wear and adjusts to keep the correct tolerance

The twoway hopper feeding paddle keeps the concrete flowing

Four-function remote control via cable



REMOTE CONTROL

Part # 1107001
Five - function radio remote control unit with output and adjustment





Tow with confidence with the smooth towing torsion bar suspension, adjustable tow bar, surge brake, full compliement of tow lights and reflectors and easy roll and leveling jack stand.

Setups



Kit for Concrete Pumping Part # 1106123


- 9 steel pipe dn 4" X 10' HD
- 1 Rubber hose dn 4" X 10' HD
- 1 Steel bend dn 4", 90° HD
- 1 steel bend dn 4", 45° HD
- 12 Heavy Duty coupling dn 4"
- 12 gasket for Heavy Duty coupling dn 4"
- 2 cleaning ball



Kit for **Shotcreting** Part # 1106124

- 2 rubber hose diam. 33' Victaulic 2" Victaulic 2"
- 1 rubber hose diam. 33' Victaulic 2" cam dn 50 mm
- 1 complete hopper grid 5/8" mesh
- 1 spritz beton gun dn 50 with fast Geka coupling 3/4" for air
- 1 reduction cone dn 4" 50 mm (2") Heavy Duty I= 39"
- 1 hanging belt for hose
- 2 cleaning ball for hose diam. 2"
- 1 Heavy Duty coupling dn 4"
- 2 gasket for Heavy Duty coupling dn 4"
- 3 Victaulic coupling dn 2"
- 6 gasket for Victaulic coupling dn 2"
- 1 gasket for cam coupling dn 50





Kit for Fast Setting Additives Part # 1107172

- Pumping Unit (hydraulic motor and screw pump with 3/4" manifold)
- 20' hose for connection to additive tank
- Spray gun for shotcreting ID 50 complete with cam coupling, 3/4"
 Geka coupling and connector for additive
- · Control panel with manual/automatic additive flow adjustment (proportional to concrete output)

for pumps and mixers



- ✓ Rotors and stators
- ✓ Mixer paddles
- ✓ Spray guns/wands
- ✓ Spray gun components
- ✓ Hoses







Compressor for spraying mortar, stucco, etc.

The most reliable in its class



MAXIMUM MOTOR PERFORMANCE



Separate cooling of the electric motor and compressor allows for continuous duty and a long life.

Power supply	1 HP
Flow rate	9 CF/m
Maximum pressure	60 PSI
Heavy Duty service	110 V






REPLACEMENT OF THE AIR FILTER



Air filter replacement is quick and easy.

ONE PIECE CRANKSHAFT



One piece compressor motor crankshaft produces maximum mechanical performance effortlessly.

	ACCL	SOURIES & SPAR	LI	AN	TO		
Part number	Applications Kit	Accessories	Small 50	Koine 4	Koine 35	Step 120	Prestige
1107005	000	Fireproofing, mortar and cementituous stucco gun kin • Spray gun • Deflector Ø 12 mm (1/2") for traditional mortar • Deflector Ø 10 mm (3/8") - 14 mm (9/16") for premixed mortars • 50' of hose Ø 25 mm (1") for material with cam couplings • 53' of air hose Ø 13 mm (9/16") with Geka couplings • No. 1 Spray gun cleaner • No. 1 sponge Ø 30 mm (1-1/4")	•				
1107006	00	Injection kit • Pressure meter unit and pressure gauge • Brass fitting M. 1" F. 3/4" • Small 50 spray gun with 1 deflector with hose connector Ø 16 mm (5/8") • 33' of hose Ø 25 mm (1") for material with cam couplings • 16' of hose Ø 25 mm (1") for material with cam couplings • Spray gun cleaner and sponge Ø 30 mm (1-1/4")	•				
1107009	QQ	Painting kit • Spray gun + deflectors Ø 5 - Ø 6 mm (1/4") • 33' of hose Ø 19 mm (3/4") mm for material with cam couplings • 52' of air hose Ø 13 mm (9/16") with Geka couplings • Spray gun cleaner and sponge Ø 25 mm (1") • Hose reduction device	•				
1107010	000	Stucco and waterproofing gun kit • Spray gun • Deflectors Ø5 (3/16") - Ø6 (1/4") - Ø8 (3/8") - Ø12 mm (1/2") • Deflector with hose connector Ø 16 mm (5/8") • 33' + 16' of hose Ø 25 mm (1") for material with cam couplings • 53' of air hose Ø 13 mm (9/16") with Geka couplings • Spray gun cleaner and sponge Ø 30 mm (1-1/4")	•				
1107091		Self-Levelling and grout kit No. 1 remote control (wire lenght 53') No. 1 rotor D8-1.5 ECO (rif.1107031) No. 1 Stator D8- 1.5 (rif.1107028) No. 1 electric device for remote control plugging No. 1 self levelling mixer		•			

	ACCLO	SUMILS & SPAI		77 (7	J		
Part number	Stators and rotors	Accessory	Small 50	Koine 4	Koine 35	Step 120	Prestige
1107030		Stator D 8-1.5 ECO Color: green Max. aggregate size 3/16" Flow rate CF/h** 76 at 400 RPM Working pressure 220 PSI	•	•	•		Applications
1107031	-3	Rotor D 8-1.5 ECO – GREEN	•	•	•		NIC Stations and
1107084		Stator ECO STAR Color: violet Max. aggregate size 3/32" Flow rate CF/h** 40 at 400 RPM Working pressure 290 PSI	•	•	•		TOLOR &
1107085		Rotor ECO STAR – VIOLET	•	•	•		
1107032		Stator for fine materials • Color: yellow	•				
1107033		Rotor for fine materials - YELLOW	•				
N/A		Stator R 7 • Color: Tan • Max. aggregate size 3/16" • Flow rate CF/h** 127 at 400 RPM		•			
N/A	2000	Rotor R 7 with turbo drive tab - tan		•			
N/A		Stator R 8 • Color: black • Max. aggregate size 3/16" • Flow rate CF/h** 169 at 400 RPM		•			
N/A		Rotor R 8 with turbo drive tab - black		•			

<u> </u>		SURILS & SPAR					
Part number	Stators and rotors	Accessory	Small 50	Koine 4	Koine 35	Step 120	Prestige
1107077		Stator 2L6 • Color: yellow • Max. aggregate size 1/4" • Working pressure 435 PSI				•	•
1107078		Rotor 2L6				•	•
1107110		Stator IM25L for mortar and grout Color: blue Flow rate I/min Max. aggregate size 3/8" Working pressure 220 PSI				•	•
1107111		Rotor IM25L				•	•
1107081		Stator 60.12 for self-leveling and high flow grouts • Color: yellow • Flow rate 12 CY/h • Max. aggregate size 3/8" • Working pressure 220 PSI				•	•
1107083		Rotor 60.12				•	•

	110000	OTTIES & STITE					
Part number	Mixers	Accessory	Small 50	Koine 4	Koine 35	Step 120	Prestige
1107542		Standard mixer paddle		•	•		
1107100		Standard mixer paddle		•	•		
1107541	395	Mixer paddle for light materials		•	•		
1107590		Mixer paddle for light materials		•	•		ă.
1107517	88.	Turbo mixer for increasing shear		•	•		Mixers / Spray Guns
1107597	Service of the servic	Mixer paddle for self-levelling mortars		•	•		
3223347		Scraping rod for mixing chamber			•		
3224916		Scraping rod for mixing chamber	***************************************	•	•		
3223349		Cleaning scraper for mixing chamber		•	•		
3223352		Motor gearbox coupling		•	•		
3223354		Rotor adjustment tool		•	•		

	ACCLO	OCKIES & SPAK		TUT	O		
Part number	Spray guns	Accessory	Small 50	Koine 4	Koine 35	Step 120	Prestige
1107011		Stucco and waterproofing guns	•		•		
1107540		Fireproofing and mortar gun kit	•	•	•	•	•
1107549		5' overhead wand for fireproofing	•	•	•	•	•
1107568		Spray gun Ø 25 mm (1") F	•	•	•	•	•
1107577		Spray gun for mortar and fireproofing Ø 35 mm (1-3/8")		•		•	•
1107504		Tuck-pointing gun kit. Use with vibrating hopper	•				

	7.37	COLOGOTHE	G OI		LAILI	U		
Part number	Components for spray gun	s Accessory	1107540	1107011	1107549	1107568	1107577	
1107551		10-piece kit: Deflector Ø 10 mm (3/8") (Duse) for premixed plaster	•		•	•	•	
1107552	0	10-piece kit: Deflector Ø 12 mm (1/2") (Duse) for premixed plaster	•		•		•	
1107553		10-piece kit: Deflector Ø 14 mm (9/16") (Duse) for premixed plaster	•		•	•	•	
1107554	_	10-piece kit: Deflector Ø 16 mm (5/8") (Duse) for premixed plaster	•		•	•	•	
1107557		5-piece kit: Deflector Ø 10 mm (3/8"), of polyurethane (IMER)-traditional plaster	•				•	
1107558		5-piece kit: Deflector Ø 12 mm (1/2"), of polyurethane (IMER)-traditional plaster	•				•	
1107559		5-piece kit: Deflector Ø 14 mm (9/16"), of polyurethane (IMER)-traditional plaster	•				•	
1107560		5-piece kit: Deflector Ø 16 mm (5/8"), of polyurethane (IMER)-traditional plaster	•				•	Sp
1107561		3-piece kit: Deflector Ø 5 mm (3/16") hardened steel for painting, smoothing and spacing		•				Spray Guns
1107562		3-piece kit: Deflector Ø 6 mm (1/4") hardened steel for painting, smoothing and spacing		•				Ins
1107563		3-piece kit: Deflector Ø 8 mm (3/8") hardened steel for smoothing		•				
1107564		3-piece kit: Deflector Ø 12 mm (1/2") hardened steel for spacing with the help of compressor		•				
1107604	1000 1	Kit deflectors Ø 5 (3/16") -6 (1/4") -8 (5/16") -12 (1/2") -16 mm (5/8") hardened stainless steel		•				
1107566		3-piece kit with hose connector Ø 16 mm (5/8")		•				
3209356		Eyebolt for spray gun	•		•	•	•	
3223345		Head for spray gun	•		•	•		

			JOUILLO	u OI				
Part numbe	er Components for spray gur	is	Accessory	1107540	1107011	1107549	1107568	1107577
3223348		Plastic pipe for	spray gun	•			•	
3224361		Camlock coupli	ing for spray gun Step 120					•
3226721		Head for spray	gun Step 120					•
3224701	35	Camlock coupli	ing for spray gun	•	•	•	•	
3224830	0	Gasket for Cam	nlock coupling	•	•	•	•	
3225598		🌡 Air pipe with va	alve for spray gun	•				•
3223694		Cleanout file fo	r stator/rotor and spray gun	•	•	•	•	•

		OFCOLUT	io a	OIAILL	TUTIT		
Part number	Hoses	Accessory		Part number	Hoses	Accessory	
1107529		33' of hose Ø 19 mm (3/4") mm for material with cam couplings		3224706		Cam couplings Ø 19 mm (3/4") F	
1107525		50' of hose Ø 25 mm (1") for material with cam couplings		3224701	35	Cam couplings Ø 25 mm (1") F	_
1107526		33' of hose Ø 25 mm (1") for material with cam couplings		3224492		Cam couplings Ø 50 (2") F	-
1107527		16' of hose Ø 25 for material with cam couplings		3224869		Gasket for Camlock coupling Ø 19 mm (3/4")	-
1107528		33' of hose Ø 35 mm (1-3/8") for material with cam couplings		2224020		Gasket for Camlock coupling Ø 25	-
1107533		33' rubber hose Ø 50 (2") with cam couplings		3224830		mm (1")	_
1107534		66' rubber hose Ø 50 (2") with cam couplings		3224831		Gasket for Camlock coupling Ø 35	_
1107579		66' material hose with cam		3224499		Gasket for Camlock coupling Ø 50 (2")	
		couplings for Silent 300cl 16' of material hose Ø 25 mm (1")		3225891		Gasket for Camlock coupling Ø 65 (2-1/2")	
1107074		M35/M25 with cam couplings		3224498		Camlock lever Ø 19 mm (3/4")	1
1107075		66' of material hose Ø 35 (1-3/8") M50/F35 with cam couplings					-
1107203		Material Hose Ø 50 (2") F - Ø 35 mm (1-3/8") Lenght 33'		3224498		Camlock lever Ø 25-35-50	Hoses
1107578		33' of material hose Ø 60 mm (2-3/8") with cam couplings		3225929		Repairing Camlock coupling for hose Ø 19 mm (3/4") M	
1107530		16' of air hose Ø 13 mm (9/16") with Geka couplings		3225933		Repairing Camlock coupling for hose Ø 25 mm (1") M	
1107531		33' of air hose Ø 13 mm (9/16") with Geka couplings		3225935	I	Repairing Camlock coupling for hose Ø 35 mm (1-3/8")	_
1107532	14	52' of air hose Ø 13 mm (9/16") with Geka couplings		3225937		Repairing Camlock coupling for hose Ø 50 (2") M	_
3228464		Water hose 98'		3225940		Repairing Camlock coupling for hose Ø 50 (2") M for Ø 35 hose	_

	AC	CLOSOIT	LO Q SPANI	P LUIII	J
Part number	Hoses	Accessory	Part number	Hoses	Accessory
3225930		Repairing Camlock coupling for hose Ø 19 mm (3/4") F Repairing Camlock coupling for	1107519		10-piece kit: sponge for cleaning hose Ø 25 mm (1")
3225934	0	hose Ø 25 mm (1") F	1107520		10-piece kit: sponge for cleaning hose Ø 35 mm (1-3/8") mm
3225936		Repairing Camlock coupling for hose Ø 35 mm (1-3/8") F	1107521		10-piece kit: sponge for cleaning hose Ø 50 (2") mm
3230909		Repairing Camlock coupling for hose Ø 50 (2") F for Ø 35 mm (1-3/8") hose	1107522		10-piece kit: sponge for cleaning hose Ø 60 mm (2-3/8")
3225938		Repairing Camlock coupling for hose Ø 50 (2") F	3223728		Geka coupling with hose connector Ø 18 mm (11/16")
3225941		Clamp for material hose Ø 28-35	3223615		Geka coupling with hose connector Ø 13 mm (9/16")
3225942		Clamp for material hose Ø 32-40	3224818		Geka coupling with hose connector Ø 10 mm (3/8")
3225943		Clamp for material hose Ø 39-48	3223428		Geka coupling with female thread 1"
3225944		Clamp for material hose Ø 60-76	3224382		Geka coupling with female thread 1/2"
1107565		Camlock fitting kit Ø 35 mm (1- 3/8") F-Ø 25 mm (1") M	3223636		Geka coupling with female thread 3/4"
1106178		Camlock fitting kit Ø 50mm (2")	3230172		Geka coupling with female thread 3/8"
		M-Ø 35mm (1-3/8") F	3223722		Geka coupling with male thread 1"
1107087		Cleaning kit for hose material Ø 35 mm (1-3/8")	3224203	R	Geka coupling with male thread 1/2"
1107103		Cleaning kit for hose material Ø 25 mm (1")	3223614		Geka coupling with male thread 3/4"
1107104		Cleaning kit for hose material Ø 50 (2")	3223404		Geka coupling with male thread 3/8"
1107105		Cleaning kit for hose material Ø 65 (2-1/2")	3223697	0	Geka coupling gasket
	·				

		OUTILE & STATE					
Part number	Plaster sprayers Accessories	Accessory	Small 50	Koine 4	Koine 35	Step 120	Prestige
1107016		Vibrating hopper	•				
1107510		Vibrating grate	•				
1107512		Pressure gauge	•				
1107515		Injection pressure regulator	•				
1107543		Dual diaphragm compressor	•				
1107544		50' remote control extension	•			● 220V	
1107545		53' remote control	•			● 220V	
1107569		Grate for premixed materials				•	Screw
1107574		120' remote control		•		•	Screw Pump Accessories
1107570		Pipe hook Ø 25 mm (1")	•	•	•		ries

ACCESSOTIES & STATE TAILES									
Part number	Plaster sprayers Accessories	Accessory	Small 50 Koine 4	Koine 35	Step 120	Prestige			
1107491	Kind	Vacuum kit for Koine series pumps. Vacuum not included.	•	•					
3224493		220V power cord, 66'		•	•				
1107001		Five-function radio remote control unit				•			
1107036		Vibrating grate				•			
1107086		Wired remote control (with 164' cable)				•			
1107088	Charles and The	Stator/rotor kit 2L6			•	•			
1107149		Stator/rotor kit IM25L			•	•			
1107090		Stator/rotor kit 60.12			•	•			
1107161	6	Pintle towing ring towing kit 2-3/4" x 1" mm			•	•			

ACCESSOTIES & STATE TATES							
Part number	Plaster sprayers Accessories	Accessory	Small 50 Koin	e 4 Koine 35	Step 120 Prestige		
1107207		Mechanical water meter system			•		
1107208		Hydraulic power washer			•		
1107209		AQUA CONTROL electronic water meter system			•		
3225836		Pump pressure adjustment kit			•		
3225846		Small 50 hopper cap (washing sponge Ø 40 [2-3/8"])	•				

CONCRETE Accessories

		CONCRETE Accessories				
Part number		Accessory				
1107170		Kit automatic lubrificating system				
1107171	0	Kit high pressure water jet cleaner				
1107001		Five-function radio remote control unit with output adjustment				
1107196		Hopper extension kit 380 I (rubber)				
1107197	alt.	Hopper extension kit 500 I (steel)				
		Accessories for DN100 (4")				
1107183	••	Cleaning ball for hose Ø 100 (4")				
	Accessories for DN 50 (2") - shotcreting					
1107192	56	Spritz beton gun ID50 with fast Geka coupling 3/4" for air and fast setting additive				
1107187		Reduction cone. ID 100(4")-ID 50(2") Victaulic L=1000				
1107188		Rubber hose Ø 50 (2") L.10 mt Victaulic 2" - Victaulic 2"				
1107189		Rubber hose Ø 50 (2") mm I. 10 mt Victaulic 2" - cam ID 50				
1107181		Victaulic coupling ID 2"				
1107182	88	Kit no. 5 Gaskets for Victaulic coupling ID 2"				

Machine Application Chart

	Conventional Mortar (non- premixed)	Ready-Mixed (Premixed) Mortars	Self-Levelling Underlayments	Traditional Floor Screed (dry-pack)	Shotcrete	Concrete and Micro-Concrete	Fireproofing
Koine 35	×	~	~	×	×	×	~
Koine 4	×	~	~	×	×	×	~
Small 50	~	~	~	×	×	×	~
Step-up 120 3 phase	~	~	✓	×	~	~	~
Step-up 120 Single phase	~	~	~	×	×	×	~
Prestige	~	~	~	×	~	~	~
Mortarman 120+	~	~	✓	~	~	~	~
Booster 15	×	×	~	×	~	~	×
Step 120a	×	×	~	×	~	~	×



X Not recommended



Modern Technology | OLD SCHOOL QUALITY

To download a digital copy of our full line catalog, please visit us at www.imerusa.com or call us at (800) 275-5463 to request a physical copy and general information.

