

# SILENT 300 PRESTIGE

Diesel powered screw pump for pumping and spraying

## APPLICATIONS

For mixing, pumping and spraying of mortars in bags or from silo: premixed materials, cement or gypsum based premixed materials, fireproofing, grouts, epoxies, self-leveling underlayments or repair mortars.

↓ **PRESTIGE Eco T Power**  
20 HP Diesel  
Model # 1106132



✓ Safety sensor system stops the mixing paddles if the grid is opened

✓ All the drive systems are hydraulic, very safe and very little maintenance



✓ The high capacity mixer (6.5 CF) with hydraulic drive is powerful and reliable

Innovative System  
**ECO TPOWER**

Adjusts engine RPMs according to power demands



✓ High capacity hopper (7 CF), run hard batch after batch

## Standard Equipment

- ✓ Kohler Focs 1003/3 cyl. diesel engine
- ✓ 14 CF/m compressor
- ✓ 2L6 screw pump
- ✓ 66' + 33' material hose Ø 35 mm (1-3/8")
- ✓ 16' material whip hose Ø 25 mm (1")
- ✓ 2 clean-out sponges
- ✓ 53' + 66' air hose Ø 13 mm (9/16")
- ✓ 1 hose holder fitting
- ✓ Tiltable mixer
- ✓ Hydraulic variable speed pump
- ✓ Tow package for highway use
- ✓ Metal accessory box



### OPTIONAL ELECTRONIC WATER METER



Part # 1107209  
**AQUA CONTROL** electronic water meter:  
 for quick and easy addition of metered water  
 put into the mixer for every batch.

### DIESEL MOTOR



3-cylinder, liquid-cooled diesel engine that  
 meets the latest EPA regulations and reduces  
 noise. 2400 rpm operating speed for less  
 wear and low fuel consumption.

### STANDARD PRESSURE WASHER



Part # 1107208  
 2,000 PSI pressure washer cleans  
 effectively with minimal blow-back.

### CONTROL PANEL



Anti-vibration control panel with  
 electromechanical controls  
 (Standard hour meter)

Recommended accessories for

#### Traditional & premixed mortar

- ✓ 1107036 - Vibrating screen
- ✓ 1107149 - Pumping Unit IM25L (for course aggregate)
- ✓ 1107577 - Spray gun for traditional & premixed mortar
- ✓ 1107560 - 5-piece kit up to Ø 16 mm (5/8")

#### Self-levelling floor screeds and flowable grouts

- ✓ 1107090 Pumping Unit 60.12 for self-levelling underlayments

Motor power rate ISO 3046/1-IFN	HP	20 (at 2400 rpm)
Compressor flow rate	CF/m	14
Max pumpable grain size	In.	1/4 (2L6)
Variable theoretic flow rate	CY/h	0 - 4.5 (2L6)
Max pressure	PSI	580 (2L6)
Hopper capacity	CF	7
Mixer capacity	CF	6.3
Dimensions length/width/height (mixer tilted)	In.	131.5/53.5/53
Weight	Lbs.	1,653
Sound pressure level	dB (A)	< 78

(\*) The road towing is valid only in the countries where it is allowed.