


120V Dimmable LED Strip Light - PRO-H



With the updated technology, this product is built for connecting directly to high voltage, which is 120V AC. No transformer/driver needed anymore. With the 1ft cut point and waterproof design (IP65), this truly flexible lighting can be used for many applications such as backlighting, illuminating sign letters and complex shapes.

Features

- 120VAC operation (no power supply required)
- IP65 - Suitable for wet location
- ELV dimmer compatible
- Can span long run up to 164ft
- High lumens output and high PF
- Viewing angle 120°
- Overvoltage protection
- Over temperature protection
- Customized product, all sizes available
- Fast and easy installation, saving labor costs greatly
- ETL, FCC certified
- Limited 5 years warranty




Specification

Input Voltage	120VAC		
Dimmable	ELV		
Color	4000K	BLUE	RED
Brightness	320lm/ft	60lm/ft	34lm/ft
Light Efficiency	80lm/W	15lm/W	9lm/W
Power Consumption	4W/ft		
CRI	90+		

LED Quantity	36 LEDs/ft
One Run Max	164ft
LED Chip	2835
FPC Width	5/16in
Operating Temperature	-4°F~104°F
Lumen Maintenance	50,000 hrs
IP Rating	IP65 (Wet location)

Dimension




Order Information

Model	Voltage	Color Temperature	Length(ft)
GL-LV-2835NWC-144H	120-120VAC	4000K	0-0ft
GL-LV-2835B-144F		BLUE	1-1ft
GL-LV-2835R-144F		RED	2-2ft
			3-3ft
			4-4ft
			...
			164-164ft


120V Dimmable LED Strip Light PRO-H

Connecting Accessories


Since the 120V Strip Light is a **customized** light with factory cut and assembling, the connection accessories are not sold separately. Please add the required quantity in the order.




Plug-in Power Cable
GL-LV-PC




End Cap
GL-LV-EC




Corner Connector
GL-LV-CC




Jumper Cable
GL-LV-JP-1/2
GL-LV-JP-2




Installation Accessories (Sold Separately)




Mounting Clip
GL-LV-MCL-V2



Mounting Channel
GL-LV-MCH-4




Compatible Aluminum Channel (Sold Separately)




Aluminum Channel	Series	Model No.	Accessories	Hotspot	Recommended # of Strips
A2525 LINEAR	A 2525	A-2525-AL-8-M	End cap, Mounting	No Hotspots	1 strip
3535 LINEAR	ES 3535	ES-3535-AL-8-M	End cap, Mounting, Connecting	No Hotspots	1 strip
5035 LINEAR	ES 5035	ES-5035-AL-8-M	End cap, Mounting, Connecting	No Hotspots	2 strips
7535 LINEAR	ES 7535	ES-7535-AL-8-M	End cap, Mounting, Connecting	No Hotspots	3 strips

Special Assessories (For A 2525 Only)



Aluminum Channel Mounting Options



*For more detailed Aluminum channel information, please see LED aluminum channel specification of each series.

GL LED US LIGHTING reserves the right to modify this specification without prior notices.