


LED Aluminum Channel - SLIM RECESS YD 1201



Slim Recess YD 1201 is ideal for general hotspots-free recessed mounting of most of our popular LED strip light. With black finishing and milky diffuser, YD 1201 complements a wide variety of applications.

Features

- Slim and deep
- Customizable.
- Anodized finish.
- Slim, low profile design.
- Covers and protect LED strip light.
- Manufactured with a patented frosted diffuser for maximum lumen output and wider beam distribution.



Specification

Length	24in, 94in
Internal width	0.47in
Finish	Black
Diffuser	Milky
Material	Anodized Aluminum
Installation	Recessed Mount
Accessories	End cap, Mounting Clips

Models

Model No.	Finish Color	Diffuser Type	Dimension (L x W xH)	Application
YD-1201-AL-2-M-B	Black	Milky	24x0.90x0.59in	Indoor, Outdoor
YD-1201-AL-8-M-B	Black	Milky	94x0.90x0.59in	Indoor, Outdoor

Accessories (Sold Separately)



YD 1201 End Caps
YD-1201-EC-B




ES 2315/YD 1201 Mounting Clip
ES-2315-MC




ES 2315/YD 1201 Mounting Clip
YD-1201-PC-B

Installation Diagram




Mounting Options


Recessed Mount



Recessed mounting with Mounting Clips
















Recessed mounting with Screws



Recessed mounting with 3M Tape

Compatible LED Strip Lights

	Series	Model No.	Width	LED Quantity	Light Filling Level	Hotspots Level
	INFINITE	GL-3528-120-xxxxK-24V-IP20-CC	0.39in	34 LEDs/ft	Full	No Hotspot
	ECO	GL-3528-112-xxxxK-xxV-IPxx	0.39in	34 LEDs/ft	Full	No Hotspot
	PRO	GL-3528-240-xxxxK-24V-IPxx	0.39in	73 LEDs/ft	Full	No Hotspot
	LEGEND	GL-2835-240-xxxxK-24V-IPxx	0.39in	73 LEDs/ft	Full	No Hotspot
	NARROW	GL-3528-120-xxxxK-12V-IP20-5MM	0.2in	36 LEDs/ft	Full	No Hotspot
	COB	GL-COB-480-xxxxK-24V-IP20	0.39in	145 LEDs/ft	Full	No Hotspot
	TUNABLE WHITE	GL-2835-240-CCT-24V-IP20	0.39in	73 LEDs/ft	Full	No Hotspot
	FOR BREAD	GL-2835-60-2500K-12V-IP20-B	0.39in	18 LEDs/ft	Full	Hotspot
	FOR MEAT	GL-2835-60-2900K-12V-IP67-M	0.39in	18 LEDs/ft	Full	Hotspot
	RGB HIGH BRIGHT	GL-5050-60-RGB-xxV-IPxx	0.39in	18 LEDs/ft	Full	Hotspot
	RGB SUPER BRIGHT	GL-3535-120-RGB-24V-IPxx	0.39in	34 LEDs/ft	Full	Partial Hotspot
	RGBW	GL-5050-96-RGB+xxxxK-24V-IP20	0.47in	29 LEDs/ft	Full	Hotspot
	RGB DIGITAL	GL-5050-60-DIG-12V-IPxx	0.39in	18 LEDs/ft	Full	Hotspot

Light Filling Level



Full



Partial

Hotspots Visible Level



No Hotspot



Partial Hotspot



Hotspot

Note:

We recommend to use two, or more, LED strips in a shallow channel that has internal width that is greater than .8in to prevent partial filling.

Note:

When LEDs are used with aluminum channel there may be hot spots. The more depth of a channel, and/or density of a LED, can help reduce visible hot spots