LED Downlight

GL LED LLC

Recessed downlights are designed for all ceiling applications, both residential and commercial, like education, healthcare, hospitality, offices, retail, parking, etc. The screwless connection and easy for loop in/out design saves your installation cost. Perfect choice for a capricious consumer.



FOCU 3 1/2" Cutout

Popular market trend, low glare and multi-functional recessed downlight No. GL-DL-FC-8-W-xxxxK/DTW-38

Features & Benefits

- CREE COB LED
- Die casting aluminum heatsink
- 120V AC input (single unit driver)
- Anti-glare, UGR<19
- Triac/ELV dimming control
- · Spring clips easy installation
- Air-tight, IP44
- Ultraviolet (UV) + Infrared (IR) free light
- Passive cooling system without fans
- 24" twistlock connection cable
- Low profile, suitable for insulation ceiling
- Replace 50-70W Halogen
- Damp location



Order Options

Color Temperature

- 2700K
- 3000K
- 4000K
- Dim to warm

Power

- 8W	
Beam Angle	
- 38°	

All Direction Tilt - 30°






UGR<19







Brightness				
ССТ	2700K	3000K	4000K	Dim to warm (2000K-3000K)
Brightness	533lm	574lm	615lm	39-936lm
CRI	90+	90+	90+	95+