G.L. LED US LIGHTING

LED Linear Light - SINGLE RUN L8050



LED linear light is exclusively designed for designer and architect with imagination and personal style. LED linear light adopt premium aluminum profile, different dimension and size. No need to worry about any assembling work. They come in one piece as the finished product. The Single Run is a one-piece plug-and-play product that evenly provides abundant light coverage for all your business and personal needs.

Features

- Suitable for home, office and any appropriate indoor space.
- Quick and easy to install.
- Smooth and soft lighting effect, no dark dot and shadow at the lighting area.
- Connect to line voltage (100-277VAC) directly.

- Various installation: Suspended, Surfece and Recessed Mounting.
- 0-10V Dimming.
- Lifespan (hrs): 50,000hr.
- 5 year warranty.



Specification

Length	4	ft	8ft		
Input Voltage	AC 100-2	77V 50Hz	AC 100-277V 60Hz		
Power	36W		60W		
Power Factor	0.95+				
Color	3000K	4000K	3000K	4000K	
Brightness	3260lm	3560lm	6280lm	6300lm	
Finish	Black,White				
Installation	Suspended, Surface and Recessed Mounting				

LED Type	2835		
Reflector	Milky		
Dimmable	0-10V Dimming		
Beam angle	e 110°		
CRI	80+		
IP Level	IP40(Non-waterproof)		
Pre-Wired	5 wires, 18AWG		
Pre-wired	copper core, L, N, G, DIM+, DIM-		

Order Information




GL LED US LIGHTING reserves the right to modify this specification without prior notices.

G.L. LED US LIGHTING

Packaging

Product	Net Weight	Gross Weight /CTN	Inner size (L x W x H)	Carton size (L x W x H)	Package
L8050 4ft	5.46lb	39.97lb	5032 x 51/8 x 43/16 in	50 ²³ ⁄ ₃₂ x 15 ²⁷ ⁄ ₃₂ x 9½6 in	1pcs/inner box, 6 inner boxes/carton
L8050 8ft	9.92lb	56.22lb	96¾ x 5½ x 41⅓ in	96 ¹⁵ ⁄16 x 10 ²⁵ ⁄32 x 93⁄8 in	1pcs/inner box, 4 inner boxes/carton

Dimension



Accessories & Functional Accessories (Sold Separately)



Single Run L8050 - Suspension Canopy Kit SCK-PF-H2-X2-X / SCK-NPF-H1-X2-X

Mounting Options




Single Run L8050 - Recessed Kit L-8050-RCK




Single Run L8050 - Surface Mount Kit **L-8050-SFMK**




Emergency Driver YH29FA-25VL



Suspended Mounting with Power Feed Canopy Kit - Type A2



Recessed Mounting with Recessed Kit



Suspended Mounting with Non-Power Feed Canopy Kit - Type D2

Surface Mounting with Surface Mount Kit

*These diagrams are for references only. For more canopy kit options please visit LED Linear Light Accessories on website.

GL LED US LIGHTING reserves the right to modify this specification without prior notices.