LED Module Light - Tiny



Features

- · Ensures excellent transmittance and uniform lighting
- Compact size
- Single Color with natural color projection
- · Safe Operation with 12 VDC
- Wide viewing angle for even light flux
- · Capable of wet exposed applications with durable weather protective molding, IP68
- Easy installation with double sided 3M tape and screw holes for extra security
- 160° wide angle allows the light to spread evenly and eliminates hot spots
- · CE, UL, RoHS, SASO, INNOBIZ Approved

Specification

| Input Voltage | 12VDC Samsung | | | |
|---------------------|-----------------------|--|--|--|
| Chip | | | | |
| Wire Size | 20 AWG, 2 wire | | | |
| Dimensions | 0.47" x 0.31" x 0.19" | | | |
| Length | 8 modules/ft | | | |
| Work Temperature | -22F-158F | | | |
| Storage Temperature | -40F-167F | | | |
| Waterproof Rate | IP68 | | | |
| Warranty | 5 years | | | |

| Model | Color Temperature | Lens | Viewing Angle | Lumen/pc | Watts/Module | Qty/Bag |
|-----------------------|-------------------|---------|---------------|----------|--------------|---------|
| Z1U-V05-W(S)-a6-024-3 | 6500K | Frosted | 160° | 25 | 0.24W | 200 |