## **Maxiflo Pressure Regulator**



Ahead Of The Game

The **Maxiflo** Pressure Regulator has been designed for one step reduction of water pressure.

Designed for: Poultry Watering Systems, Animal Watering Systems and Irrigation Systems

It effectively reduces water wastage and assists suppression of water hammer.

The **Maxiflo** Pressure Regulator is flexible in coping with a wide range of inlet pressure fluctuations.

The large diaphragm area gives the **Maxiflo** a particularly sensitive characteristic, essential in many installations where fine control of outlet pressure is required.

Multiple installations of the **Maxiflo** pressure regulator in parallel gives increased secondary flow.



## **Regulator Specifications**

Height	6 in (150mm)	Temperature Range	3° - 100° F (1° - 40° C)
Diameter	6 in (150mm)	Inlet	1⁄2" BSP
Weight	27 ounces (770g)	Outlet	¾" BSP
Material	Acetyl Copolymer	Maximum Inlet Pressure	300 psi

Model No.	Main Seat	<b>Effective Ration</b>	Outlet Pressure Range	
6001	5/32"	900:1	4 in to 7 ft hd	1⁄4 psi to 3 psi
6002	1/4"	300:1	18 in to 20 ft hd	¾ psi to 8 psi
6003	3/8"	100:1	4 ft to 30ft hd	1 ½ psi to 13 psi
6012	3/8"	100:1	17 ft to 40ft hd	7 ½ psi to 17 psi



Manor Farm, Pulham, Dorchester, Dorset, DT2 7EE

www.quillproductions.co.uk

(T) 01258 818239 (E) sales@quillprod.com