

# 6784R Neo Grab™



## Cotton material Neoprene coating

### DESCRIPTION

- Fully coated
- Topstitched edge
- Rough finish over entire surface
- Antibacterial and anti-odour treatment
- Cut and sewn
- High performance polyethylene (HPPE)



### BENEFITS

- A flexible glove that offers great dexterity and with good resistance to tearing
- Protects the hand from oils, hydrocarbons, grease and abrasion, with unrivaled, long living grip
- Impermeable for working in damp or greasy environments
- Surface provides tactile feel and better grip
- Greater hygiene
- Wrist well protected
- Low-soil colour

### RECOMMENDED FOR THESE RISKS:

Chemicals  
Abrasion

### RECOMMENDED FOR THESE LINES OF WORK:

Chemical industry / Acid components  
Petrochemistry

### AVAILABLE SIZES

10/L

### LENGTH

Dependent on size, in mm (flat)

355

### PACKAGING

Pairs or pieces per pack/box

12/36

### COLOUR OF SUPPORT/COATING

Blue

### Distributor Details:



**SENTINEL**  
Laboratories Ltd

Units 12-13 Lindfield Enterprise Park  
Lewes Road, Lindfield  
RH16 2LH

Tel: 01444-480444 Fax: 01444-484045  
Email: sales@sentinel-laboratories.com  
Web: www.sentinel-laboratories.com

### RECOMMENDATIONS FOR USE

- Store away from light and humidity
- Rinse the gloves in running water before removing, using a neutral detergent if necessary
- Do not wear gloves when there is a risk of entanglement by moving parts of machines.



HYDROCHLORIC ACID 36% KEROSENE  
0 1 2 3 4 5 6  
METHANOL CAUSTIC SODA 4%  
0 1 2 3 4 5 6

3221

[ Updated 01/02/2010 ]

EC compliance certificate delivered by the notified body 0072 IFTH - Institut Français du Textile et de l'Habillement  
Avenue Guy de Collongue - 69134 Ecully Cedex - France

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.

