# 730 Nitri-Solve®





RECOMMENDED FOR THESE RISKS:

#### Oils

Chemicals

Abrasion

RECOMMENDED FOR THESE LINES OF WORK:

Chemical industry / Solvents

Food industry

### **Distributor Details:**



Units 12-13 Lindfield Enterprise Park Lewes Road, Lindfield RH16 2LH Tel: 01444-484044 Fax: 01444-484045 Email: sales@sentinel-laboratories.com Web: www.sentinel-laboratories.com Unsupported, coton flock Nitrile coating

## DESCRIPTION

- Fully coated
- Scalloped edge
- Textured finish
- Without special treatment
- Anatomical shape
- Does not contain silicones
- Approuved for food handling
- Ambidextrous

## BENEFITS

- A flexible glove that absorbs perspiration
- Protects the hand from oils, hydrocarbons, grease and abrasion, with effective long lasting grip (more information on www.chemrest.com)
- · Impermeable for working in damp or greasy environments
- Surface provides better grip
- Lower allergy risks
- · Designed for easy movement and continuous wear
- Can easily be one-hand used
- Wrist well protected

AVAILABLE SIZES	7/S • 8/M • 9/L • 10/XL • 11/XXL
LENGTH Dependent on size, in mm (flat)	330
PACKAGING Pairs or pieces per pack/box	6/72
COLOUR OF SUPPORT/COATING	Green
THICKNESS in mm	0.38

#### **RECOMMENDATIONS FOR USE**

- Store away from light and humidity
- Rinse the gloves in running water before removing, using a neutral detergent if necessary
- Do not wear gloves when there is a risk of entanglement by moving parts of machines.
- · Potential allergens: thiazole





 A - METHANOL
 D - DICHLO


 0 12 34 56
 0 12 34 56

 J - N-HEPTANE
 K - CAUSTI

 0 1 2 34 56
 0 1 2 34 56

 HYDROCHLOR. ACID 36%
 KEROSENE

 0 1 2 34 56
 0 1 2 34 56







EC compliance certificate delivered by the notified body 0321 SATRA House - Rockingham Road, Kettering - Northampshire NN16 9JH - United Kingdom

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.