878 Best® Butyl



Unsupported Butyl coating

DESCRIPTION

- · Fully coated
- Rolled cuff
- Standard finish
- Without special treatment
- Anatomical shape
- · Available by individual pair in polybag with eyelet



BENEFITS

- A thin, light glove with a "second skin" feel
- Protects the hand from a wide array of chemical hazards (more information on www.chemrest.com)
- Impermeable for working in damp or greasy environments
- Cuff prevents dirt from entering the glove
- · Lower allergy risks
- Designed for easy movement and continuous wear
- Packaging that helps finding the right model in displays
- Wrist well protected
- Low-soil colour

RECOMMENDED FOR THESE RISKS:
Chemicals
RECOMMENDED FOR THESE LINES OF WORK:
Chemical industry / Acid components
Police & Army
Chemical industry / Acetone and Ketone components

AVAILABLE SIZES	8/M • 9/L • 10/XL • 11/XXL
LENGTH Dependent on size, in mm (flat)	350
PACKAGING Pairs or pieces per pack/box	1/12
COLOUR OF SUPPORT/COATING	Black
THICKNESS in mm	0,70

RECOMMENDATIONS FOR USE


- Store away from light and humidity
- Rinse the gloves in running water before removing, using a neutral detergent if necessary
- Do not wear gloves when there is a risk of entanglement by moving parts of machines.
- Potential allergens: thiazoles and thiurames

Distributor Details:



Units 12-13 Lindfield Enterprise Park Lewes Road, Lindfield RH16 2LH

Tel: 01444-480444 Fax: 01444-484045 Email: sales@sentinel-laboratories.com Web: www.sentinel-laboratories.com



ABRASION CUTTING 0 1 2 3 4 0 1 2 3 4 5

TEARING PUNCTURE 0 1 2 3 4 0 1 2 3 4





B - ACETONE 0 1 2 3 4 5 <u>6</u> I - ETHYL ACETATE

K - CAUSTIC SODA 40% 0 1 2 3 4 5 <u>6</u>

[Updated 13/10/11]

