

890E Best® Viton®



Unsupported Viton over Butyl coating

DESCRIPTION

- Fully coated
- Rolled cuff
- Standard finish
- Without special treatment
- Anatomical shape
- Available by individual pair in polybag with eyelet



BENEFITS

- A thin, light glove with a "second skin" feel
- Protects the hand from a wide array of chemical hazards (more information on www.chemrest.com)
- Impermeable for working in damp or greasy environments
- Cuff prevents dirt from entering the glove
- Lower allergy risks
- Designed for easy movement and continuous wear
- Packaging that helps finding the right model in displays
- Wrist well protected
- Low-soil colour

RECOMMENDED FOR THESE RISKS:

Cuts

RECOMMENDED FOR THESE LINES OF WORK:

Petrochemistry

AVAILABLE SIZES

9/L • 10/XL

LENGTH

Dependent on size, in mm (flat)

350

PACKAGING

Pairs or pieces per pack/box

1/12

COLOUR OF SUPPORT/COATING

Black

THICKNESS

in mm

0,70

RECOMMENDATIONS FOR USE

- Store away from light and humidity
- Rinse the gloves in running water before removing, using a neutral detergent if necessary
- Do not wear gloves when there is a risk of entanglement by moving parts of machines.
- Potential allergens: thiazoles and thiurames

Distributor Details:

SENTINEL
Laboratories Ltd

Units 12-13 Lindfield Enterprise Park
Lewes Road, Lindfield
RH16 2LH

Tel: 01444-484044 Fax: 01444-484045
Email: sales@sentinel-laboratories.com
Web: www.sentinel-laboratories.com



0120



2101

ABRASION CUTTING
0 1 2 3 4 0 1 2 3 4 5
TEARING PUNCTURE
1 2 3 4 0 1 2 3 4



DFL

A - METHANOL
1 2 3 4 5 6
J - N-HEPTANE
1 2 3 4 5 6
HYDROCHLOR. ACID 36%
1 2 3 4 5 6

D - DICHLOROMETHAN
0 1 2 3 4 5 6
K - CAUSTIC SODA 4%
1 2 3 4 5 6
KEROSENE
1 2 3 4 5 6

F - TOLUENE
0 1 2 3 4 5 6
L - SULPHURIC ACID 96%
0 1 2 3 4 5 6

[Updated 01/02/2010]

