

58-128Nitrile glove with second skin fit

Enhanced Dexterity with Light Duty Chemical Protection and ANSELL GRIP Technology™

- ERGOFORM helps support musculoskeletal health during repetitive tasks and improves worker performance
- United States Ergonomics certification
- Unique "Thin Nitrile Technology" yields a thin barrier while offering superior protection from oils and other irritant fluids
- ANSELL GRIP[™] technology for the handling of wet or oily parts providing enhanced dexterity, grip and comfort



- Automotive
- Automotive Aftermarket
- Machinery and Equipment
- Metal fabrication
- Chemical

Applications

- Body painting including surface inspection
- Applying sealers, touching up
- Press injection molding
- Equipment repair & maintenance
- Assembling and mounting components
- Painting or cleaning tools or robots
- Final assembly
- Metalwork, glass processing
- Assembly & inspection of components
- Warehousing of raw materials
- Testing







58-128 Nitrile glove with second skin fit

Key Features

- The first ergonomically certified chemical glove
- Provides quantifiable ergonomic benefits to the wearer
- Delivers high-performance musculoskeletal support
- Conforms to the shape of the wearer's hand enabling natural movement
- Maximizes worker productivity by minimizing hand fatigue and discomfort
- Reduces the risk of ergonomic injury caused by prolonged or repetitive manual tasks

Technologies





Performance Standards



























CHEMICAL AGENT	BREAKTHROUGH TIME		
n-Heptane (J)	>480		
Sodium hydroxide, 40% (K)	>480		
Ammonium hydroxide, 25% (O)	62		
Hydrogen peroxyde, 30% (P)	>480		
Hydrofluoric acid, 40% (S)	42		
Formaldehyde, 37% (T)	>480		

PERMEATION BREAKTHROUGH TIMES ACCORDING TO EN 16523-1 : 2015 (MINUTES)									
0	1	2	3	4	5	6			
< 10	10-30	30-60	60-120 120-240		240-480	> 480			
Not recommended	Splash protection		Medium protection		High protection				

Data given in the table above are based on results of laboratory tests performed on the palm area of the glove. These tests were run using standard test methods that may not adequately replicate any specific conditions of end use. Because Ansell has no detailed knowledge or control over the conditions of end use, any of these data must be advisory only, and Ansell must decline any liability.

Specifications

BRAND STYLE	DESCRIPTION	SIZE	LENGTH	COLOR	PACKAGE
AlphaTec® 58-128	Nylon, Nitrile, Ansell Grip™	7, 8, 9, 10, 11	320-328 mm/ 12-13 inches	Gray	12 pairs/polybag; 12 polybags/carton

Europe, Middle East & Africa Region

Ansell Healthcare Europe NV Riverside Business Park Blvd International, 55 1070 Brussels, Belgium T: +32 (0) 2 528 74 00 F: +32 (0) 2 528 74 01

Ansell Canada Inc 105, rue Lauder Cowansville (Québec) Q7001 Torre II.

North America Region

Ansell Healthcare Products LLC 111 Wood Avenue South. Suite 210 Iselin, NJ 08830, USA T: +1 800 800 0444 F: +1 800 800 0445

Latin America & Caribbean Region

Ansell Commercial Mexico S.A. de C.V Blvd. Bernardo Quintana No. 7001-C. BIVA. Bernardo Quintana No. 70 Q7001 Torre II. Suites 1304, 1305 y 1306. Col. Centro Sur, c.p. 76079 Queretaro, Qro. Mexico T: +52 442 248 1544 / 248 3133

