HyFlex® 11-624



Mechanical Protection



Cut Protection



Medium

IDEAL APPLICATIONS

- Assembling metal parts and components
- Assembly of white goods
- Automotive
- Glass manufacturing
- Handling of sharp-edged objects, pre-assembling, cutting of small dry or lightly oiled parts and maintenance.
- Plastics injection and moulding

PRIMARY INDUSTRIES














STANDARDS AND CERTIFICATIONS



CATEGORY II

FEATURED TECHNOLOGY



EXTRA FEATURES

High flexibility, strong cut resistance

DESCRIPTION

- HyFlex® 11-624 gloves provide comfort and dexterity. Easy to wear during long working hours, they also offer users a "cool feeling".
- The special formulation of the polyurethane coating gives the gloves flexibility and fit, as well as a secure grip on dry to slightly oily pieces for sure handling in a wide range of environments.
- The liner is made with a yarn structure containing Dyneema $^{\mathbb{R}}$, the world's strongest fiber $^{\mathbb{T}M}$. It therefore offers strong cut resistance for the safe handling and assembly of sharp pieces.

PRODUCT DETAILS

Construction	Knitted
Liner material	Lycra® Nylon Dyneema®
Gauge	13
Coating material	Polyurethane
Finishing	Palm coated
Cuff style	Knitwrist
Colour	Black and grey
EN Sizes	6,7,8,9,10,11
Length (mm)	220 - 270
Packaging	12 pairs in a bag; 12 bags in a carton

Print date 21-10-2019

