


HyFlex® 11-840

MECHANICAL PROTECTION

 MULTI-PURPOSE

 LIGHT

STYLE #	CONSTRUCTION	GAUGE	LINER MATERIAL	COATING MATERIAL	FINISHING	CUFF STYLE	COLOUR	EN SIZE	LENGTH MM	PACKAGING
11-840 	Knitted	15	Spandex Nylon	Foam nitrile	Palm coated	Knitwrist	Black and grey	6, 7, 8, 9, 10, 11	200-270	12 pairs in a bag, 12 bags in a carton



Extreme durability and superior fit for precision handling in abrasive applications

PRIMARY INDUSTRIES



IDEAL APPLICATIONS

- Assembly of small & medium parts
- Feeding the lines
- General handling
- Raw materials reception
- Screwing & unscrewing

DESCRIPTION

- The tough 1.1 mm FORTIX® nitrile foam coating (patent pending) offers EN Abrasion Level 4 protection, with up to three times the abrasion performance of other lightweight, knit-dipped gloves.
- The FORTIX® coating is 20% more breathable than earlier formulations, for cooler, drier hands and less sweat.
- Matching the natural contours of the hand, the snug, second-skin liner is tailored to create a more comfortable wearing experience: at the base of the little finger (added comfort), across the fingertips (superior tactility), and through the palm (greater dexterity).
- With its balance of robust abrasion performance, enhanced comfort and high dexterity the HyFlex® 11-840 is an ideal solution for workers who move between tasks.
- Silicone-free material means no transfer of silicone contaminants to metal parts prior to painting.

REMARKS

- Fit for special purpose

FEATURED TECHNOLOGY

Fortix®



EN 388
4231

CATEGORY II

Distributor Details:

SENTINEL
Laboratories Ltd

Units 12-13 Lindfield Enterprise Park
Lewes Road, Lindfield
RH16 2LH
Tel: 01444-484044 Fax: 01444-484045
Email: sales@sentinel-laboratories.com
Web: www.sentinel-laboratories.com

Ansell

Multi-purpose

Print date 18-10-2015

Glove material

- Foam nitrile (Coating material)
- Spandex (Liner material)
- Nylon (Liner material)

Possible Harmful ingredientsSensitizers

- Natural rubber proteins (in knitwrist elastic)

Only a very small number of users may be sensitised to this ingredient in the glove and hence may develop irritant and/or allergic contact reactions.

Reach Regulation 1907/2006

For more information, please consult the REACH statement on the Ansell website

Properties

- Excellent abrasion resistance
- Excellent breathability
- Very comfortable

EN Test Data**Abrasion resistance:**

Performance level 4

Blade cut resistance:

Performance level 2

Tear resistance:

Performance level 3

Puncture resistance:

Performance level 1

European conformity

Gloves conform to the requirements of the European Directive 89/686/EEC and to the European standards EN 420:2003 + A1:2009 and EN 388:2003

They are categorised in "Intermediate Design" (= Protection against intermediate risks).

EC-Type Examination Certificate for the final product by
CENTEXBEL (0493)
Technologiepark 7
B-9052 Zwijnaarde

Application - Limitations of use

Do not use against flames or temperatures $- 25^{\circ}\text{C}$ or >math>100^{\circ}\text{C}</math>

Do not use against chemicals; the glove is not liquidproof

Storage

Keep away from sources of ozone or ignition.

Keep out of direct sunlight; store in a cool and dry place.

Construction	Gauge	Liner material	Coating material	Finishing	Cuff style	Colour	EN Size	Length mm	Packaging
Knitted	15	Spandex Nylon	Foam nitrile	Palm coated	Knitwrist	Black and grey	6, 7, 8, 9, 10, 11	200-270	12 pairs in a bag; 12 bags in a carton

The length of the gloves is below the EN requirements for total minimum glove length. Hence, the glove is called 'Fit for special purpose'

Distributor Details:

SENTINEL
Laboratories Ltd

Units 12-13 Lindfield Enterprise Park
Lewes Road, Lindfield
RH16 2LH
Tel: 01444-484044 Fax: 01444-484045
Email: sales@sentinel-laboratories.com
Web: www.sentinel-laboratories.com

Ansell