

SHOWA BEST
GLOVE

Manufacturers of Atlas® and N-DEX®

NSK-26

OIL AND CHEMICAL RESISTANT
FULLY-DIPPED NITRILE
SPASH RESISTANT SLEEVE
DELICATE OPERATIONS



Chemical Resistant Glove

Characteristics

- Extended Sleeve of Thin Nitrile with Thickness of 0.50 mm (≈ 2mils)
- Textured Grip
- Length: 65 cm (26 in)
- Sizes: 8 Medium
9 Large
10 Extra-Large
11 XX-Large

Description

Best Nitr-Solve Knit (NSK26) is a 65 cm (26 in) long glove, made from dipped nitrile over a cotton liner. NSK26 protects the hand and arm, as well as providing comfort and touch sensitivity. The durable Nitrile coating offers excellent protection against a wide range of chemical substances. The Nitrile-coated sleeve provides splash protection from a wide range of chemicals. The rough textured finish ensures excellent grip. An elastic band and grommet holds the sleeve up on the arm. This glove is durable and chemical resistant with an extended liquid-proof splash resistant sleeve. Its antibacterial treatment provides greater hygiene. Launder at 40°C (104°F) using a neutral detergent.

Suggested Applications:

- Oily Greasy Applications
- Refineries
- Sewer Cleaning
- Deep-Sea Fishing
- Protection from Fuels
- Painting
- Splash Protection

This list of suggested applications is partial and based on laboratory testing of glove performance.

For a complete list of suggested applications, visit our website:

www.showabestglove.com

Cat. III
CE
0 1 2 0

EN 388
-2003-
4 1 1 1

Abrasion 0 1 2 3 4	Tear 0 1 2 3 4
Blade Cut 0 1 2 3 4 5	Puncture 0 1 2 3 4

EN 374-3
-2003-
A J K

A (Methanol) 0 1 2 3 4 5 6	Hydrochloric Acid (36%) 0 1 2 3 4 5 6
J (Heptane) 0 1 2 3 4 5 6	Kerosene 0 1 2 3 4 5 6
K (Sodium Hydroxide) 0 1 2 3 4 5 6	

ANSI/ISEA 105-2005 Performance

Abrasion Resistance 0 1 2 3 4 5 6
Cut Resistance 0 1 2 3 4 5
Puncture Resistance 0 1 2 3 4 5

Distributor Details:

SENTINEL
Laboratories Ltd

Units 12-13 Lindfield Enterprise Park
Lewes Road, Lindfield
RH16 2LH
Tel: 01444-484044 Fax: 01444-484045
Email: sales@sentinel-laboratories.com
Web: www.sentinel-laboratories.com