

## Neoprene-dipped coating on a double insulating liner for improved resistance in hot conditions

- The glove combines the flexibility and chemical resistance of neoprene with the comfort and heat resistance of a soft thermal liner.
- The glove is designed to protect the users in applications where thermal and chemical risks are present.



### Industries

- Machinery and Equipment
- Metal fabrication
- Chemical

### Applications


- Press work
- Handling materials with sharp or rough edges
- Production line support & maintenance
- Unexpected leakages spills or other releases

#### Key Features

- Neoprene glove with a double insulating liner to better resist to heat and cold environment
- Designed to protect the users in applications where thermal and chemical risks are present
- Excellent mechanical and chemical properties. Unaffected by detergents and cleaning solutions. Excellent protection against greases and oils. Superior flexibility and grip
- Comfortable insulating double liner. Provides protection from intermittent contact with hot surfaces up to 180°C
- Longer version than the 19-024 for further protection



#### Performance Standards



CHEMICAL AGENT	BREAKTHROUGH TIME		
	Palm	Cuff	
Methanol (A)	>480	201	
Sodium hydroxide, 40% (K)	>480	>480	
Sulphuric acid, 96% (L)	>480	215	
Nitric acid 65% (M)	>480	42	
Hydrogen peroxide, 30% (P)	>480	>480	
Formaldehyde, 37% (T)	>480	>480	

PERMEATION BREAKTHROUGH TIMES ACCORDING TO EN 16523-1 : 2015 (MINUTES)						
0	1	2	3	4	5	6
< 10	10-30	30-60	60-120	120-240	240-480	> 480
Not recommended	Splash protection		Medium protection		High protection	

Data given in the table above are based on results of laboratory tests performed on the palm area of the glove. These tests were run using standard test methods that may not adequately replicate any specific conditions of end use. Because Ansell has no detailed knowledge or control over the conditions of end use, any of these data must be advisory only, and Ansell must decline any liability.

#### Specifications

BRAND   STYLE	DESCRIPTION	SIZE	LENGTH	COLOR	PACKAGE
AlphaTec® 19-026	Double insulating liner, Cotton, Neoprene,	8, 10	660 mm; 26 inches	Black and Grey	• 1 pair in a bag; 12 bags in a carton

#### Europe, Middle East & Africa Region

Ansell Healthcare Europe NV  
Riverside Business Park  
Blvd International, 55  
1070 Brussels, Belgium  
T: +32 (0) 2 528 74 00  
F: +32 (0) 2 528 74 01

#### North America Region

Ansell Healthcare Products LLC  
111 Wood Avenue South,  
Suite 210  
Iselin, NJ 08830, USA  
T: +1 800 800 0444  
F: +1 800 800 0445

#### Latin America & Caribbean Region

Ansell Commercial Mexico S.A. de C.V.  
Blvd. Bernardo Quintana No. 7001-C,  
Q7001 Torre II,  
Suites 1304, 1305 y 1306,  
Col. Centro Sur, c.p. 76079  
Queretaro, Qro. Mexico  
T: +52 442 248 1544 / 248 3133

#### Canada

Ansell Canada Inc.  
105, rue Lauder  
Cowansville (Québec)  
Q7001 Torre II,  
J2K 2K8, Canada  
T: 1 800 363-8340  
F: 1 888 267-3551

Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending:  
www.ansell.com/patentmarking © 2018 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.