

Neoprene, chemical accelerator-free offering unsurpassed combination of sensitivity and durability for sterile environments

For Class 100 (ISO 5) cleanroom wet and dry applications, the TouchNTuff® 73-500 is a thin, sterile Neoprene glove that offers added tactile sensitivity and provides chemical splash resistance against a broad range of chemicals. Ideal for double donning.



- Compatible with Class 100 (ISO 5) / Grade A Cleanroom Environments
- Thin design for superior tactile sensitivity
- Broad chemical splash resistance
- Ideal for double donning
- Prevents Type I and Type IV allergies

Industries

- Pharmaceutical Manufacturing
- Medical Device Manufacturing
- Laboratory Research and Development
- Controlled and Critical Environments
- Production and Manufacturing

Recommended For

- Packaging and labeling
- Clean room cleaning and preparing
- Sample taking and processing



TECHNICAL DATA SHEET

PRODUCT INFORMATION

	73-500
Material	Neoprene (Polychloroprene)
Color	Cream
Shape	Anatomic with Curved Fingers
Cuff	Beaded with SUREFIT™ Technology
Manufacturing/QMS Audit Standards	ISO 9001:2008
Regulatory/Standards Compliance	AS/NZS 4179, ASTM D3577, ASTM D7160, Category III, CE 0086, EAC TP TC 019:2011, EN 420:2003 + A1:2009, EN 421:2010, EN 455 1-4, EN ISO 374-1:2016, EN ISO 374-5:2016, ISO 10282, ISO 11137-1:2006, ISO 13485, ISO 14001, ISO 9001, JIS T9107
Packaging	1 pair per inner poly pack; 10 inner poly packs per inner polybag; 5 outer polybags per bag; 4 bags per master bag; 1 master bag of 200 pairs per carton/case
Storage	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition
Country of Origin	Sri Lanka
Available sizes	5.5, 6.0, 6.5, 7.0, 7.5, 8.0, 8.5, 9.0
Powder Content	Powder-Free
External Glove Surface	Smooth
Sterilization Method	GAMMA irradiation (25 kGy)
Cleanroom Compatibility	Class 100/ ISO 5/ Grade A
Shelf Life	3 Years
Tested for use with Chemotherapy Drugs	Yes, in accordance with ASTM D6978 (Not listed in the US FDA 510k)
Protein Level	N/A: contains no natural rubber latex
Anti-static	Not Tested

PHYSICAL PROPERTIES

	Typical Values		Testing Method
Length (mm/in)	295 / 11.6		
Freedom from Holes	Manufacturing final release: 0.65 (Inspection level G1)		
Typical Particle Count > 0.5µm (counts / cm ²)	≤ 250		IENT-RP-CC005.4
Minimum Single Wall Palm Thickness (mm/mil)	0.10 - 0.15 / 5.90 - 5.91		
Minimum Single Wall Finger Thickness (mm/mil)	0.11 - 0.17 / 4.33 - 6.69		EN 420:2003+A1:2009 / ASTM D3767
Minimum Single Wall Cuff Thickness (mm/mil)	0.11 - 0.17 / 4.33 - 6.69		EN 420:2003+A1:2009 / ASTM D3767
	Before Ageing	During Ageing	
Ultimate tensile strength (MPa)	17	12	
Force at Break (N)	9	9	

ORDERING INFORMATION

	SIZE	5.5	6	6.5	7	7.5	8	8.5	9
73-500	REORDER NO.	73500055	73500060	73500065	73500070	73500075	73500080	73500085	73500090

For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region

Ansell Healthcare Europe NV
Riverside Business Park
Blvd International, 55
1070 Brussels, Belgium
T: +32 (0) 2 528 74 00
F: +32 (0) 2 528 74 01

Asia Pacific Region

Ansell Global Trading Center
(Malaysia) Sdn Bhd
Prima 6, Prima Avenue
Block 3512, Jalan Teknokrat 6
63000 Cyberjaya
Selangor, Malaysia
T: +603 8310 6688
F: +603 8310 6699

North America Region

Ansell Healthcare Products LLC
111 Wood Avenue South,
Suite 210
Iselin, NJ 08830, USA
T: +1 800 800 0444
F: +1 800 800 0445

Latin America & Caribbean Region

Ansell Commercial Mexico S.A. de C.V.
Blvd. Bernardo Quintana No. 7001-C,
Q7001 Torre II,
Suites 1304, 1305 y 1306,
Col. Centro Sur, c.p. 76079
Queretaro, Qro. Mexico
T: +52 442 248 1544 / 248 3133

Australia

Ansell Limited
Level 3,678 Victoria Street,
Richmond, Vic, 3121
Australia
T: +61 1800 337 041
F: +61 1800 803 578

Russia

Ahcenn PYC
123610 Poccnr, Mockba
Kpachonpechehckar
Ha6. 12, n.3, op. 1304A
Ten. +7 495 258 13 16

Technology

SUREFIT™

Cuff Roll-down Technology

Performance Standards and Regulatory Compliance



Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking © 2019 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.