

Product Description – SlipDoctors Pro-Coat Bond Adhesion Promoter enhances and improves adhesion of coatings that have an increased risk of peeling or chipping. Bond Adhesion Promoter can be mixed into a variety of coatings without altering the appearance or function of the coating. When mixed into the first coating batch, Bond Adhesion Promoter is recommended for increasing the functional life, corrosion resistance, appearance and sealer qualities of SlipDoctors’ products. Bond Adhesion Promoter can be used when overcoating previously sealed or coated surfaces, floors that cannot be sanded or etched and floors that have a questionable level of coating failure risk. Bond Adhesion Promoter reduces the chance or degree of cracking and flaking. This product also helps when top coating water base products over oil-based bottom coats.

SlipDoctors Bathtub & Shower Kit

Special Features

- Does not alter color/sheen of coating
- Oil and Water compatible
- Does not alter traction of grit-based coatings
- Increases life and function of coatings
- Reduces bonding and adhesion problems

Suggested Uses

- Metal surfaces
- Marble and Granite surfaces
- High sheen porcelain
- Terrazzo
- Composite Decking
- Concrete
- Surfaces that are hard, smooth, polished and/or glossy

Product Characteristics and Benefits

Surfaces	Dependent upon base coating choice.
Color	Clear (resembles color and shine of base coat mix) liquid additive
Mode of Application	Pre-mix into base coat prior to application (2 ounces Bond promoter per gallon of coating product)
Size	Two- and eight-ounce bottles available
Dry Time	Follow base coat recommendations (this product is generally used in first coat batch only). Will not increase or decrease dry times.
Water Resistant	N/A
Stain Resistant	N/A
Product Type	Carbon Silicon base bonding adhesion promoter
Coverage	Dependent upon base coating rates
Storage	Keep at room temperatures closed and labeled. Do not store for more than 48 hours if mixed into a coating product.
Shelf Life	1 year opened; 2 years unopened
Warranty	2 years
Removal	Wipe off and cleanse surface with soapy water and rinse if accidentally spilled.
Disposal	Dispose of according to local regulations.

Directions for Preparation, Application and Use

Read entire product label, Technical Data Sheet (TDS) and Safety Data Sheet (SDS) before using.

Safety Precautions:

- Avoid contact with eyes and inhalation of vapors.
- Immediately wash off the product with soap and water if it comes in contact with skin.
- Use product in a well-ventilated area.
- Keep away from heat, sparks and flames.
- If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Hotline at 1-800-424-LEAD or www.epa.gov/lead.

Optional Safety Equipment:

- Chemical-resistant gloves
- Clothing to cover all skin areas
- Eye protection

Surface Preparation: Use surface preparations listed for the base coating product (surface should generally be clean and dry). Use application and dry times listed by the product being used.

Application Instructions:

- Step 1** Mix two ounces bond adhesion promoter per gallon of coating product. Stir in gently until thoroughly blended.
- Step 2** Pour product into application tray and apply according to base coatings recommendations.
- Step 3** Allow first coat to dry according to recommendations of base product. Save excess leftover product and re-stir before using on second coat if done within 48 hours of original mixing.

Maintenance:

For general cleaning and maintenance, use a light pressure rinsing. For best results to remove oily deposits or other foreign matter, apply pH-neutral cleaner at recommended dilution rate and scrub lightly with a soft bristle deck brush.

Precautions & Technical Support

Please refer to Safety Data Sheet (SDS) for detailed Precautions and First Aid Instructions.

Bonding Agent Safety Data Sheet can be found at www.slipdoctors.com

Technical Support: Please contact SlipDoctors at 1-888-436-5404 or support@slipdoctors.com

Office Hours: Monday - Friday from 8:00 am - 5:00 pm CST

Warranty & Disclaimer

WARRANTY: All properly installed SlipDoctors products are guaranteed to increase the coefficient of friction of your surface for two years (provided surface preparation and cleaning procedures are followed and no contaminants are present). If at any time during the warranty period the treated surface should lose its coefficient of friction, SlipDoctors shall at its option replace any product that proves defective. This warranty applies only to the product itself. Seller shall not be liable for any injury, loss or damage direct or consequential, arising out of the use or the inability to use the product. Before using, Buyer shall determine the suitability of the product for the intended use, and the Buyer assumes all risk and liability whatsoever in connection therewith. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by Seller and Buyer. Buyer assumes all risks and responsibility associated with disposal. SlipDoctors cannot eliminate all possibilities of slip-and-fall accidents. Please visit www.slipdoctors.com to find further warranty information. KEEP OUT OF REACH OF CHILDREN.