

Product Description – SlipDoctors’ Maintain Grip is a specialized cleaner for use on surfaces previously treated with our Stone Grip anti-slip treatment. Maintain Grip is an effective cleaner designed to break down oils, grease and other contaminants on the surface and in the pores, and effectively removes hardened grease build-up. Maintain Grip works to renew the microscopic treads, providing anti-slip traction to wet and dry surfaces. Maintain Grip can be used for daily cleaning and to remove heavy duty grease build-up in commercial, residential and industrial areas.

SlipDoctors’ Maintain Grip

Special Features

- Interior & Exterior use
- Breaks Down Oil and Grease
- Fast & Easy Application
- Made for use with Stone Grip
- NFS Certified
- Safe for Use in Food Processing Areas
- Maintains & Renews Traction

Suggested Uses

- Residential, Commercial & Industrial
- Food Processing Establishments
- Restaurants
- Schools
- Hospitals
- Hotels
- Patios, Showers & Restrooms

Product Characteristics and Benefits

Surfaces	Quarry tile, glazed tile, ceramic tile, porcelain tile and concrete
Color	N/A
Mode of Application	Mop
Size	Gallon
Application Temperature	Above 40°F (4°C) surface temperature; evaporation may occur at higher temperatures
Dry Time	N/A
Water Resistant	N/A
Stain Resistant	N/A
Product Type	Commercial Strength Cleaner
Coverage	Up to 40,000 sq.ft./gallon after dilution
Storage	Store in dry area at ambient room temperature of 72°F / 22°C
Shelf Life	5 years
Removal	N/A
Disposal	Dispose of container and unused contents in accordance with local, state, and federal regulations.

Directions for Preparation, Application and Use

Read entire product label, Technical Data Sheet (TDS) and Safety Data Sheet (SDS) before using.

Safety Precautions:

- Keep children and small pets out of area until surface has been thoroughly dried.
- Gloves should be worn at all times.

Recommended Safety Equipment:

- Chemical-resistant gloves
- Closed Toe Shoes
- Eye protection

Notice: Do not use on any synthetic surface such as wood, laminate, vinyl, VCT or fiberglass. Not recommended for use on glass, polished marble, granite or terrazzo with marble chips, as it may remove shine from highly polished surfaces. If product gets on aluminum, remove promptly with a clean, wet towel.

Surface Preparation: Wipe up any spills and sweep debris from floor surface. Since floor tile compositions differ greatly among manufacturers, **ALWAYS** test product on a small, inconspicuous area for acceptance, appearance and results prior to application over the entire area.

Dilution Ratio and Cleaning Instructions by Floor Type

Surface Type	Dilution	Cleaning Instructions
Normally Soiled Floors	1 oz of Maintain Grip to 1 gallon of warm water	Apply diluted solution to floor surface using a wet mop. Aggressively scrub the floor with a deck brush. Do not allow the solution to dry on the surface. Mop up soiled solution or squeegee to drain. Rinse or damp mop floor surface clean using potable water. Dry floor surface using a dry mop or squeegee.
Concrete & Heavily Soiled Floors	4 oz of Maintain Grip to 1 gallon of warm water	Apply diluted solution to floor surface using a wet mop and allow to stand on area to be cleaned for 3-5 minutes. Aggressively scrub the floor with a deck brush. Do not allow the solution to dry on the surface. Mop up soiled solution or squeegee to drain. Rinse or damp mop floor surface clean using potable water. Dry floor surface using a dry mop or squeegee.

Precautions & Technical Support

Please refer to **Safety Data Sheet (SDS)** for detailed **Precautions and First Aid Instructions**.
Maintain Grip Safety Data Sheet can be found at www.slipdoctors.com

Technical Support: Please contact SlipDoctors at 1-888-436-5404 or cs@slipdoctors.com

Office Hours: Monday - Friday from 8:00 am - 5:00 pm CST