

## Technical Data Sheet

**Product Description-** Polish Grip is a professional-grade penetrating sealer designed to provide anti-slip protection on unsealed natural stone, polished porcelain tile, polished marble, polished granite, concrete and other surfaces. This easy-to-apply treatment forms an invisible barrier that creates surface tension, increasing traction and improving resistance to spills and stains. Once applied, the lustrous natural shine of your highly polished surface remains unchanged. For use on interior and exterior surfaces.

### SlipDoctors™ Polish Grip

#### Special Features

- Use on Interior & Exterior Surfaces
- Water, Stain & Slip Protection
- Increases the Coefficient of Friction
- Weather Resistant
- One product = Multiple uses
- Retains Natural Color and Shine
- Easy to Apply
- Safe in Food Areas

#### Suggested Uses

- Residential & Commercial Use
- Hotels, Motels & Resorts
- Senior Living Facilities
- Restaurants
- Kitchens & Bathrooms
- Tiled Swimming Pool Decks
- Patios
- Highly Polished Stone Surfaces

### Product Characteristics and Benefits

<b>Surfaces</b>	Granite, marble, natural stone, porcelain tile, concrete, ceramic tile, slate, limestone, grout, terrazzo, travertine, glazed tile, quarry tile
<b>Color</b>	Clear
<b>Mode of Application</b>	Clean white towel, microfiber towel, paint roller/brush or Polish Grip Applicator
<b>Size</b>	Pint and Gallon
<b>Application Temperature</b>	Surface temperature above freezing
<b>Dry to Touch</b>	Immediately after treatment
<b>Light Traffic</b>	4-6 hours
<b>Cure Time</b>	up to 72 hours
<b>Recoat</b>	1 hour
<b>Water Resistant</b>	Yes
<b>Stain Resistant</b>	Yes
<b>Product Type</b>	Penetrating Sealer
<b>Coverage</b>	Up to 300 sq. ft. (28 m <sup>2</sup> ) /pint and up to 2,400 sq. ft. /gallon (223 m <sup>2</sup> )
<b>Storage</b>	Tightly sealed, upright in original container in a well-ventilated area that is climate controlled at up to 78°F (25°C)
<b>Shelf Life</b>	1 year
<b>Treatment Life</b>	3-12 months, depending on type of surface and amount of foot traffic
<b>Warranty</b>	One year
<b>Removal</b>	N/A
<b>Disposal</b>	Dispose of container and unused contents in accordance with local, state and federal regulations.

## Directions for Preparation, Application and Use

Read entire product label, Technical Data Sheet (TDS) & Safety Data Sheet (SDS) before using. Polish Grip anti-slip sealer should not be diluted or thinned in any way.

### Surface Preparation:

- Clean surface thoroughly with a pH neutral cleaner.
- Surface must be clean and dry before application.
- Do not apply if it has rained in the last few days or if humidity level is high.
- Protect exposed surfaces including wood, carpet, metal & landscaping.

### New Installation Application Instructions:

- Step 1** Sample Testing: Due to variations in substrates, performing a sample test is recommended to ensure maximum performance and suitability for the intended use. Test product in an inconspicuous area before full application. Minimal shading may occur temporarily until fully cured and first cleaning.
- Step 2** Do not thin or dilute. Apply evenly to surface until damp using a clean white towel or microfiber towel. Leave on surface for 3 to 5 minutes for maximum penetration.
- Step 3** Remove all excess product with a clean white towel, microfiber towel or carpet bonnet before product dries.
- Step 4** Any excess product residue that dries on the surface can be removed by re-applying a small amount of Polish Grip to the area and immediately wiping off excess while wet.
- Step 5** If a second application is desired, allow at least 1 hour before applying.
- Step 6** Polish Grip will fully cure in 24-72 hours, depending upon conditions.

**Maintenance:** Clean regularly using a pH-neutral cleaner. For best results, re-apply annually to renew slip-resistance.

## Precautions & Technical Support

**Please refer to Safety Data Sheet (SDS) for detailed Precautions and First Aid Instructions.**

Polish Grip Safety Data Sheet can be found at [www.slipdoctors.com](http://www.slipdoctors.com)

**Technical Support:** Please contact SlipDoctors at 1-888-436-5404 or [support@slipdoctors.com](mailto:support@slipdoctors.com).

**Office Hours:** Monday - Friday from 8:00 am - 5:00 pm CST.

## Warranty & Disclaimer

**WARRANTY:** All properly installed SlipDoctors products are guaranteed to increase the coefficient of friction of your surface for one year (provided surface preparation and cleaning procedures are followed and no contaminants are present). If at any time during the warranty period the treated surface should lose its coefficient of friction, SlipDoctors shall at its option replace any product that proves defective. This warranty applies only to the product itself. Seller shall not be liable for any injury, loss or damage direct or consequential, arising out of the use or the inability to use the product. Before using, Buyer shall determine the suitability of the product for the intended use, and the Buyer assumes all risk and liability whatsoever in connection therewith. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by Seller and Buyer. Buyer assumes all risks and responsibility associated with disposal. SlipDoctors cannot eliminate all possibilities of slip-and-fall accidents. Please visit [www.slipdoctors.com](http://www.slipdoctors.com) to find further warranty information. KEEP OUT OF REACH OF CHILDREN.

Revised 2/20