

Technical Data Sheet

Product Description – SlipDoctors Primer is a premium high-performance, fast-drying, corrosion resistant primer containing rust inhibitive pigments for interior and exterior applications. SlipDoctors Primer adheres tightly to clean metal may be used as a barrier coat to allow vinyls, epoxies or strong solvent-based topcoats to be applied. This product is recommended to be used with SlipDoctors Tuff Grip and Dura Grip non-slip paints.

SlipDoctors Primer

Special Features

- Interior and Exterior Surfaces
- Corrosion Resistant
- Fast Drying
- Excellent Adhesion and Flexibility
- Rust Inhibitive
- VOC Compliant

Suggested Uses

- Residential & Commercial Use
- Metal
- Steel
- Aluminum
- Wood
- Concrete

Product Characteristics and Benefits

Surfaces	Metal, steel, aluminum, wood and concrete
Color	Gray
Mode of Application	SlipDoctors 3/8" nap roller, paint gun or sprayer
Container Size	1 gallon, 5 gallon
Application Temperature	40°F - 90°F (4°C - 32°C) and at least 5°F (3°C) above the dew point
Dry Time	30 – 60 minutes or until tacky; coating can be applied once primer is tacky
Water Resistant	Yes
Stain Resistant	Yes
Product Type	Oil-Based Primer
Coverage	400 sq.ft./gallon
Storage	Store in a well-ventilated area at room temperature.
Shelf Life	2 years
Warranty	2 years
Removal	Paint thinner
Disposal	Dispose of container and unused contents in accordance with local, state and federal regulations.

Directions for Preparation, Application and Use

Read entire product label, Technical Data Sheet (TDS) & Safety Data Sheet (SDS) before using.

Safety Precautions:

- Use in a well-ventilated area.
- Highly flammable, keep away from open flames.
- If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Hotline at 1-800-424-LEAD or www.epa.gov/lead.

Recommended Safety Equipment:

- Chemical-resistant gloves
- Eye protection
- Mask

Surface Preparation: The surface must be clean, free of dust, grease, wax, soap residue, peeling paint, mold and mildew. The surface should be thoroughly degreased. Solvent wipe and/or detergent clean surfaces before application. Sandblast or wire-brush surfaces to remove rust, mill scale or other hard-to-remove contaminants. For optimum adhesion and corrosion resistance, metal should be iron or zinc phosphate treated.

Application Instructions:

- | | |
|---------------|--|
| Step 1 | Always test a small area before full application. |
| Step 2 | Use a paint shaker or hand stir to thoroughly mix primer before applying. Stir occasionally during use. No thinning required. |
| Step 3 | Apply with 3/8" nap roller or spray with paint gun or air sprayer. For best results, one thin coat is recommended. Coating may be applied after 30-60 minutes or when tacky. |
| Step 4 | Clean spills, splatters, tools and other equipment promptly with mineral spirits. |

Precautions & Technical Support

Please refer to Safety Data Sheet (SDS) for detailed Precautions List and First Aid Instructions
Primer Safety Data Sheet can be found at www.slipdoctors.com

Technical Support: Please contact SlipDoctors at 1-888-436-5404 or support@slipdoctors.com.
Office Hours: Monday - Friday from 8:00 am - 5:00 pm CST

Warranty & Disclaimer

WARRANTY: All properly installed SlipDoctors products are guaranteed to increase the coefficient of friction of your surface for 2 years (provided surface preparation and cleaning procedures are followed and no contaminants are present). If at any time during the warranty period the treated surface should lose its coefficient of friction, SlipDoctors shall at its option replace any product that proves defective. This warranty applies only to the product itself. Neither the seller nor the manufacturer shall be liable for any injury, loss or damage direct or consequential, arising out of the use or the inability to use the product. Before using, user shall determine the suitability of the product for the intended use, and the user assumes all risk and liability whatsoever in connection therewith. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by seller and manufacturer. Buyer assumes all risks and responsibility associated with disposal. SlipDoctors cannot eliminate all possibilities of slip-and-fall accidents. Please visit www.slipdoctors.com to find further warranty information.

Rev. 10/18