

1. Product and Company Information

Product Code: S-CT-TOPCLR1G
Product Name: TOPCOAT PART A BASE GAL CLEAR
Trade Name: SLIPDOCTORS HIGH GLOSS TOPCOAT – PART A
Company Name: SlipDoctors
2101 Midway Road, Suite 350
Carrollton, TX 75006 U.S.A.
Emergencies Involving Spills, Leaks
Fires, Exposures, or Accidents
Emergency Contact: CHEMTREC: (800)424-9300

Phone Number:
(972) 999-9998

2. Hazards Identification

Flammable Liquids, Category 3
Target Organ Systemic Toxicity (single exposure), Category 3
Toxic To Reproduction, Category 1B
Aquatic Toxicity (Acute), Category 3



GHS Signal Word: **Danger**

GHS Hazard Phrases: H226 - Flammable liquid and vapor.
H302 – Harmful if swallowed.
H315 – Causes skin irritation.
H319 – Causes serious eye irritation.
H332 – Harmful if inhaled.
H360 - May damage fertility or the unborn child.
H402 - Harmful to aquatic life.

GHS Precaution Phrases: P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P241 - Use explosion-proof electrical/ventilating/lighting/ equipment.
P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.
P271 - Use only outdoors or in a well-ventilated area.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.

GHS Response Phrases: P301+330+331 – IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Get medical aid.
303+361+353 - IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention.
P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P332+313 - If skin irritation occurs, get medical advice/attention.
P337+313 - If eye irritation persists, get medical advice/attention.
P370+378 - In case of fire, use water spray, dry chemical, carbon dioxide, or alcohol-resistant foam.
P403+235 - Store in cool/well-ventilated place. Store locked up.
P501-Contact a licensed professional waste disposal service to dispose of this material.

GHS Storage and Disposal Phrases: P403+235 - Store in cool/well-ventilated place. Store locked up.
P501-Contact a licensed professional waste disposal service to dispose of this material.

Potential Health Effects (Acute and Chronic):

Inhalation: Chronic inhalation may cause effects similar to those of acute inhalation. Material is irritating to mucous membranes and upper respiratory tract. Harmful if inhaled. Inhalation of high concentrations may cause central nervous system effects characterized by nausea, headache, dizziness, unconsciousness and coma. Vapors may cause dizziness or suffocation.

Skin Contact: May be harmful if absorbed through the skin. Prolonged and/or repeated contact may cause irritation and/or dermatitis.

SLIPDOCTORS HIGH GLOSS TOPCOAT – PART A / PAGE 2

Eye Contact: Causes eye irritation. Causes redness and pain.
Ingestion: May be harmful if swallowed. May be harmful if inhaled. May cause irritation of the digestive tract. May cause gastrointestinal irritation with nausea, vomiting and diarrhea. May cause central nervous system depression, characterized by excitement, followed by headache, dizziness, drowsiness, and nausea. Advanced stages may cause collapse, unconsciousness, coma and possible death due to respiratory failure. Aspiration of material into the lungs may cause chemical pneumonitis, which may be fatal.

3. Composition/Information on Ingredients

CAS #	Hazardous Components (Chemical Name)	Concentration
Proprietary	Polyester poly-urethane	50.0 – 60.0%
123-86-4	Butyl acetate	38.0 – 48.0%
108-65-6	Propylene glycol methyl ether acetate	1.0 – 5.0%

4. First Aid Measures

In Case of Inhalation: If inhaled, remove to fresh air. If breathing is difficult, give oxygen. Remove from exposure and move to fresh air immediately. Get medical aid.

In Case of Skin Contact: Flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. If skin irritation occurs, get medical advice/attention.

In Case of Eye Contact: Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid immediately.

In Case of Ingestion: Never give anything by mouth to an unconscious person. Rinse mouth with water. Do NOT induce vomiting. Get medical aid.

Note to Physician: Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area. Treat symptomatically and supportively.

5. Fire Fighting Measures

Suitable Extinguishing Media: Use water spray, dry chemical, carbon dioxide, or alcohol-resistant foam. For large fires, apply water from as far as possible. Use very large quantities (flooding) of water applied as a mist or spray; solid streams of water may be ineffective. Cool all affected containers with flooding quantities of water.

Fire Fighting Instructions: Use water spray to cool unopened containers. Protective Equipment: Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes.

Flammable Properties and Hazards: Specific Hazard(s): Flammable Liquid. Emits toxic fumes under fire conditions. During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion. Use water spray to keep fire-exposed containers cool. Flammable liquid and vapor. Vapors are heavier than air and may travel to a source of ignition and flash back. Vapors can spread along the ground and collect in low or confined areas. Vapor may travel considerable distance to source of ignition and flash back. Container explosion may occur under fire conditions. Forms explosive mixtures in air.

6. Accidental Release Measures

Steps To Be Taken In Case Material Is Released Or Spilled: Personal precautions.
Use personal protective equipment.
Spills/Leaks: Control runoff and isolate discharged material for proper disposal. Use water spray to cool and disperse vapors and protect personnel.

7. Handling and Storage

Precautions To Be Taken in Handling: Avoid contact with skin and eyes. Normal measures for preventive fire protection. Avoid inhalation of vapor or mist. Keep away from sources of ignition - No smoking. Take measures to prevent the buildup of electrostatic charge.

Precautions To Be Taken in Storing: Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep away from heat, sparks, and open flame.

SLIPDOCTORS HIGH GLOSS TOPCOAT – PART A / PAGE 3

8. Exposure Controls/Personal Protection

CAS #	Partial Chemical Name	OSHA TWA	ACGIH TWA
Proprietary 123-86-4	Polyester poly-urethane Butyl acetate	N/E PEL: 150 ppm	N/E TLV: 150 ppm STEL: 200 ppm
108-65-6	Propylene glycol methyl ether acetate	N/E	N/E

**Respiratory Equipment:
(Specify Type):**

For higher level protection use type OV/AG/P99 (US) or type ABEK-P2 (EU EN 143) respirator cartridges. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU). Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls.

Eye Protection:

Safety glasses with side shield. For a higher degree of protection, wear chemical splash goggles.

Protective Gloves:

Wear appropriate protective gloves to prevent skin exposure, such as butyl rubber or nitrile rubber.

Other Protective Clothing:

Wear appropriate protective clothing to prevent skin exposure.

**Engineering Controls:
(Ventilation, etc.)**

Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Use adequate general or local exhaust ventilation to keep airborne concentrations below the permissible exposure limits.

**Work/Hygienic/Maintenance:
Practices:**

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. Wash thoroughly after handling. Wash contaminated clothing before reuse.

9. Physical and Chemical Properties

Physical States:

Gas Liquid Solid

Flash Point:

81°F

Boiling Point:

252°F

Explosive Limits:

LEL: 1.7 UEL: 7.5

Weight Per Gallon:

8.5 +/- .25

Vapor Pressure (mm Hg):

8.4 @ 68°F

Vapor Density:

Heavier than Air

Evaporation Rate:

Slower than Ether

Percent Volatile:

52 (Vol)

10. Reactivity and Stability

Stability:

Unstable Stable

Conditions To Avoid –

Heat, flames and sparks

Instability:

Incompatibility - Materials To

Bases. Strong oxidizing agents.

Avoid:

Hazardous Decomposition Or

Nature of decomposition unknown.

Byproducts:

Possibility of Hazardous

Reactions:

Will occur Will not occur

11. Toxicological Information

Toxicological Information:

No information found.

Carcinogenicity/Other

Information:

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SLIPDOCTORS HIGH GLOSS TOPCOAT – PART A / PAGE 4

12. Ecological Information

General Ecological Information: No data available
Persistence and Degradability: No data available
Bioaccumulative Potential: No data available
Mobility in Soil: No data available

13. Disposal Considerations

Waste Disposal Method: Dispose of as unused product. This material may be burned in a chemical incinerator equipped with an afterburner and scrubber. Observe all federal, state, and local environmental regulations. Contact a licensed professional waste disposal service to dispose of this material. Dispose of any unused product.

14. Transport Information

LAND TRANSPORT (US DOT): Limited Quantity – Used for 1 gallon containers when shipped in the United States of America
DOT Proper Shipping Name: UN1263, Paint Related Material, 3, PG III – 5 Gallon pails



**Marine Transport
IMDG Shipping:** UN1263, Paint Related Material, 3, PG III



**AIR TRANSPORT (ICAO/IATA)
IATA Shipping Name:** UN1263, Paint Related Material, 3, PG III



15. Regulatory Information

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS #	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
Proprietary	Polyester poly-urethane	No	No	No
123-86-4	Butyl acetate	No	Yes 5000 lb	No
108-65-6	Propylene glycol methyl ether acetate	No	No	No

All components in this product are listed in the TSCA Inventory List.

V.O.C. MIXED: 3.25 LBS/GL (389 GMS/L)

SLIPDOCTORS HIGH GLOSS TOPCOAT – PART A / PAGE 5

16. Other Information

Revision Date: 1/5/2024

Additional Information About This Product:

Hazardous Material Information System III (U.S.A)

Health: 2

Flammability: 3

Reactivity: 0

Personal Protection: *

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by SlipDoctors and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.