

EXTRA FINE CLEAR SPRAY

TECHNICAL DATA SHEET

SlipDoctors Extra Fine Clear Spray is an epoxy aerosol spray that provides a clear, hard, finely textured finish to help prevent slips and falls. It is virtually invisible, barefoot friendly and paw friendly, lead-free and chemical resistant. Ideal for use on both interior and exterior surfaces, and for areas where water is present and slippery conditions exist. This convenient, easy-to-apply aerosol spray is the perfect solution to treat small or irregularly shaped surfaces, and can be used on vinyl, linoleum, wood and many other surfaces.

Special Features


- Interior & Exterior Use
- Barefoot Friendly
- Increases Traction
- Durable
- Easy to Clean
- Weather Resistant
- Fast & Easy Application

Suggested Uses

- Residential & Commercial Use
- Wet Areas
- Entrances/Exits
- Restrooms
- Wood Stairs
- Wood Decks
- Foyers

Product Characteristics and Benefits

| | |
|-------------------------|---|
| Surfaces | Vinyl, VCT, wood, laminate, linoleum and many other surfaces. |
| Color | Clear |
| Mode of Application | Aerosol Spray |
| Container Size | Net Wt. 11.0 oz / 311 g metal aerosol can |
| Application Temperature | 70-90°F (21-32°C) |
| Recoat | Approximately 1 hour at 77°F (25°C) |
| Dry Time | 6-12 hours |
| Water Resistant | Yes |
| Stain Resistant | Yes |
| Product Type | Epoxy |
| Coverage | Up to 20 sq.ft./can |
| Storage | Store in dry area at ambient room temperature of 72°F (22°C). |
| Shelf Life | Unused: Up to 5 years; Used: 1 year |
| Warranty | 2 years |
| Removal | Paint thinner |
| Disposal | Dispose of container and unused contents in accordance with local, state and federal regulations. |



Precautions & Technical Support

Please refer to Safety Data Sheet (SDS) for detailed Precautions and First Aid Instructions. Extra Fine Clear Spray Safety Data Sheet can be found at www.slipdoctors.com

Technical Support:

Please contact SlipDoctors at support@slipdoctors.com



EXTRA FINE CLEAR SPRAY

TECHNICAL DATA SHEET

Directions for Preparation, Application and Use

Read entire product label, Technical Data Sheet (TDS) and Safety Data Sheet (SDS) before using.

| | |
|------------------------------|--|
| Safety Precautions | <ul style="list-style-type: none"> • Extra Fine Non-Slip Spray must be used in a well-ventilated area. • Never use Extra Fine Clear Spray near an open flame. • If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Hotline at 1-800-424-LEAD or www.epa.gov/lead |
| Recommended Safety Equipment | <ul style="list-style-type: none"> • Chemical-resistant gloves • Eye protection • Mask |
| Surface Preparation | <p>Varies by surface. Please see chart below for preparation for specific surfaces. ALWAYS: Test a small area for color compatibility and adhesion. For best results, spray between 70-90°F / 20-32°C. Applying SlipDoctors Extra Fine Clear Spray below 50°F/10°C will cause the paint to spray and/or dry improperly. Dry time decreases with higher temperatures and increases with lower temperatures.</p> |
| Application Instructions | <p>Step 1: TEST: Extra Fine Clear Spray should be tested on a small inconspicuous area before full application.</p> <p>Step 2: MIXING: Mix contents of can well by shaking until the ball rattles within the can. Once ball rattles, continue to shake vigorously for 2-3 minutes. During use, shake intermittently for 10 seconds to keep product mixed.</p> <p>Step 3: APPLICATION: Spray 6-12 inches away from surface in a sweeping motion during application. When applying, note that 2-3 light coats will cure, protect and look better than one heavy coat.</p> <p>Step 4: If spray stops or is irregular, turn can upside down and spray for 2-3 seconds to clear nozzle. Wipe tip, shake can and resume. IMPORTANT: Before storing partial can, clean valve immediately after use. To clean: Hold can upside down and spray until only clear gas comes out (approximately 3 seconds), then wipe tip and store. If spray nozzle becomes clogged, remove and clean in lacquer thinner.</p> <p>Step 5: CLEAN UP: If overspray occurs, area can be cleaned with paint thinner.</p> |
| Maintenance | <p>For best results, to remove oily deposits or other foreign matter, apply pH-neutral cleaner at recommended dilution rate and scrub lightly with a soft bristle brush. For general cleaning and maintenance, use a light-pressure rinsing.</p> |



Warranty & Disclaimer

WARRANTY: All properly installed SlipDoctors products are guaranteed to increase the coefficient of friction of your surface for two (2) years (provided surface preparation and cleaning procedures are followed and no contaminants are present). If at any time during the warranty period the treated surface should lose its coefficient of friction, SlipDoctors shall at its option replace any product that proves defective. This warranty applies only to the product itself. Neither the Seller nor the Manufacturer shall be liable for any injury, loss or damage direct or consequential, arising out of the use or the inability to use the product. Before using, Buyer shall determine the suitability of the product for the intended use, and the Buyer assumes all risk and liability whatsoever in connection therewith. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by Seller and Buyer. Buyer assumes all risks and responsibility associated with disposal. SlipDoctors cannot eliminate all possibilities of slip-and-fall accidents. Please visit www.slipdoctors.com to find further warranty information. KEEP OUT OF REACH OF CHILDREN.

