

# PRIMER CLEAR

## TECHNICAL DATA SHEET

**SlipDoctors® Primer Clear** is a premium high-performance, water-based acrylic primer for indoor and outdoor applications. SlipDoctors® Primer Clear acts as a barrier coat to allow most clear, water-based coatings to be applied. This product is recommended for use with SlipDoctors water-based coatings.

### Special Features

- Interior / Exterior Surfaces
- Fast Drying
- Excellent Adhesion and Flexibility
- Low Odor
- Non-Toxic, Water-based
- Easy to Apply

### Suggested Uses

- Residential / Commercial Use
- Wood
- Concrete
- Fiberglass
- Decks / Stairs
- Walkways / Aisles

### Product Characteristics and Benefits

Surfaces	Concrete, Painted Concrete, Wood, Fiberglass
Color	Clear
Container Size	1 gallon
Application Temperature	Surface temp is between 50-90°F (10-32°C); Must be >5°F (-15°C) above dew point.
Dry Time	30 – 60 minutes or until tacky; coating can be applied once Primer is tacky.
Water Resistant	Yes
Stain Resistant	Yes
Product Type	Acrylic Polymer Latex
Coverage	300 sq.ft./gallon
Storage	Room temperature in a well-ventilated area; Protect from freezing.
Shelf Life	Unopened 2 years; Opened 1 year
Warranty	2 years
Removal	Paint stripper or acetone.
Disposal	Dispose of container and unused contents in accordance with local, stated, and federal regulations.



### Precautions & Technical Support

**Please refer to Safety Data Sheet (SDS) for detailed Precautions and First Aid Instructions.** Primer Clear Safety Data Sheet can be found at [www.slipdoctors.com](http://www.slipdoctors.com)

### Technical Support:

Please contact SlipDoctors at [support@slipdoctors.com](mailto:support@slipdoctors.com)



# PRIMER CLEAR

## TECHNICAL DATA SHEET

### Directions for Preparation, Application and Use

*Read the entire product label, Technical Data Sheet (TDS) & Safety Data Sheet (SDS) before using.*

#### Safety Precautions

- Use in a well-ventilated area.
- If you scrape, sand, or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Hotline at 1-800-424-LEAD or [www.epa.gov/lead](http://www.epa.gov/lead).

#### Suggested Safety Equipment

- Chemical-resistant gloves
- Eye Protection
- Mask

#### Surface Preparation

- Surface must be clean, free of dust, grease, wax, soap residue, peeling paint, mold, and mildew.
- Solvent wipe and/or detergent clean surfaces before application.
- Sandblast or wire-brush surfaces to remove rust, mill scale or other hard-to-remove contaminants.
- Surface should be thoroughly degreased.

#### Application Instructions

- Step 1:** Always test a small area before full application.
- Step 2:** Use a drill mixer or hand stir to thoroughly mix Primer Clear before applying. Stir occasionally during use. No thinning required.
- Step 3:** Apply with 3/8" nap roller or spray with paint gun or air sprayer. For best results, one thin coat is recommended. Coating may be applied after 30-60 minutes or when tacky.
- Step 4: CLEAN UP:** While wet, equipment may be cleaned with soap and water. Once dried, equipment may be cleaned with a solvent such as xylene.

### Warranty & Disclaimer

**WARRANTY:** All properly installed SlipDoctors products are guaranteed to increase the coefficient of friction of your surface for two (2) years (provided surface preparation and cleaning procedures are followed and no contaminants are present). If at any time during the warranty period the treated surface should lose its coefficient of friction, SlipDoctors shall at its option replace any product that proves defective. This warranty applies only to the product itself. Neither the Seller nor the Manufacturer shall be liable for any injury, loss or damage direct or consequential, arising out of the use or the inability to use the product. Before using, Buyer shall determine the suitability of the product for the intended use, and the Buyer assumes all risk and liability whatsoever in connection therewith. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by Seller and Buyer. Buyer assumes all risks and responsibility associated with disposal. SlipDoctors cannot eliminate all possibilities of slip-and-fall accidents. Please visit [www.slipdoctors.com](http://www.slipdoctors.com) to find further warranty information. KEEP OUT OF REACH OF CHILDREN.

