



FLOOR

ACACIA VALLEY™
COLORBODY™ PORCELAIN

 **daltile®**
IMAGINE WHAT'S POSSIBLE™



Coverphoto features Ark 9 x 36 and 6 x 36 field tile in a random linear pattern on the floor.
 Above photo features Aler 9 x 36 field tile in a random linear pattern on the floor.

The Look of Exotic Hardwood with the Performance of Tile

Rich in detail and color, Acacia Valley™ is designed to replicate the exotic visual of Acacia wood, which is often associated with high-end furniture. Because it was created with Tru-Edge™ technology, Acacia Valley can be installed with minimal grout joints, further enhancing the natural hardwood look. It also is designed with durability and performance in mind allowing it to be used in any room, including bathrooms and kitchens. Acacia Valley gives any space the sophistication and style of expensive hardwood with the durability and versatile use of porcelain tile.

- VISUAL APPEAL
 - Large plank sizes can be used together to create a typical hardwood visual
 - Tru-Edge™ allows for tighter grout joints and a more wood-like installation
- WARM, UNIQUE COLOR PALETTE
 - Available in natural and rich hues for enhanced design appeal
- HIGH PERFORMANCE
 - Unlike hardwood, can be used in wet areas, such as bathrooms and kitchens



PRE-CONSUMER
 RECYCLED MATERIALS



MADE IN THE U.S.A.



TRU-EDGE

All or select items within this series are made in the USA. For more information, visit daltile.com/AcaciaValley.



FIELD TILE



ASH 6 x 36 AV 05, 9 x 36 AV 13



ARK 6 x 36 AV 06, 9 x 36 AV 14



ALDER 6 x 36 AV 07, 9 x 36 AV 15



RIDGE 6 x 36 AV 08, 9 x 36 AV 16

TILE PATTERNS



ALTERNATING



ALTERNATING
with 2 sizes





HERRINGBONE
with 2 sizes

ACACIA VALLEY™

COLORBODY™ PORCELAIN

SIZES

			Thickness	Sq. Ft. per Carton	Pieces per Carton
	9 x 36 Field Tile (AV 13, AV 14, AV 15, AV 16)	(8-7/8" x 35-1/4") (22.50 cm x 89.50 cm)	3/8"	13.02	6
	6 x 36 Field Tile (AV 05, AV 06, AV 07, AV 08)	(5-3/4" x 35-1/4") (14.00 cm x 89.50 cm)	3/8"	12.78	9

FLOOR APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level- Interior	N/A	✓
Wet & Level- Interior	0.42	✓
Exterior Applications; Pool Decking & Other Wet Areas with Minimal Footwear	0.60	
Ramps & Inclines	0.65	

A DCOF value of 0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A1371-2012, Section 9.6. For more information about DCOF and the DCOF ActiTest™, visit dalTile.com/DCOF.




OTHER APPLICATIONS

	Suitable
Walls/Backsplashes	✓
Countertops	✓
Pool Linings	

APPLICATION NOTES:

Suitable for exterior applications in freezing and non-freezing climates when proper installation methods are followed.


TRIM

	Type	Number	Size	Pieces per Carton
	Bullnose	S-43H9	3 x 18	16
	Cove Base*	S-36C9TB	6 x 12	22
	Cove Base Outcorner*	SC-36C9TB	1 x 6	15

*Cove base and cove base outcorner trim are clay body ceramic suitable for exterior applications in non-freezing climates only.

Bullnose, cove base and cove base corner trim are intended to coordinate with floor field tile in the standard 90-degree installation position.

INSTALLATION

Grout Joint Recommendation	Shade Variation
1/8" (3/16" when used in a staggered brick-joint pattern, overlap not to exceed 33%)	 Random (V4)

TEST RESULTS

	ASTM #	Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 275 lbs
Scratch Hardness	MOHS	8.0
Chemical Resistance	C650	Resistant

NOTES

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to dalTile.com/LargeTiles form for information.

Strong random shading enhances the natural beauty of this product. To achieve optimal results, tile should be selected from multiple cartons and shading arranged planned prior to installation.

Special care should be taken when grouting with dark pigmented colors. A grout release is recommended to prevent finely powdered pigments from lodging in the pores of the surface. Use of a latex modified thin-set is recommended for installation.

Since there are variations in all fired ceramic products, tile and trim supplied for your particular installation may not match these samples. Final color selection should be made from actual tiles and trim and not from tile samples or color reproductions. Manufactured in accordance with ANSI A1371 standards.

Water, oil, grease, etc. create slippery conditions. For applications with exposure to these conditions require extra caution in product selection. Not for use on ramps.

For additional information refer to "Factors to Consider" at dalTile.com/Factors.



DESIGNED TO HELP EARN LEED™ CREDITS. Form our detailed information, visit dalTilegreenworks.com.

SCAN QR CODE FOR PRODUCT INFORMATION

Get a QR Code reader at: GETDALTILE.COM



7834 C.F. Haw n Freeway, Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of DalTile® products and information, visit our website at dalTile.com.



IMAGINE WHAT'S POSSIBLE™

© 2016 Dal-Tile Corporation (8/16)